Product data sheet Characteristics

H224NRBVW

Safety switch, heavy duty, fusible, 200A, 2 poles, 60 hp, 240 VAC/250 VDC, NEMA 3R, bolt-on hub, neutral, viewing window

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 1,600.00 USD



Main

Main		<u> </u>
Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	
Device application	Heavy application	
Disconnect Type	Fusible disconnect	- 1
Factory Installed Neutral	Neutral (factory installed)	
Phase	3 phase	: <u>.</u> ū
Number of Poles	2	
Current Rating	200 A	
Voltage Rating	250 V DC 240 V AC	10 FO
Enclosure Rating	NEMA 3R galvannealed steel	
Maximum Horse Power Rating	15 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 25 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 60 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 40 hp 250 V at DC	i po

Complementary

Mounting Type	Surface	
Wiring configuration	3-wire	
Wire Size	AWG 6250 kcmil copper or aluminium	5
Tightening torque	275 lbf.in (31.07 N.m) 0.020.20 in² (13.3127 mm²) (AWG 6250 kcmil)	
Depth	8.25 in (209.55 mm)	
Width	17.13 in (435.10 mm)	
Height	29 in (736.60 mm)	ـــــــــــــــــــــــــــــــــــــ
Net Weight	54.50 lb(US) (24.72 kg)	
		· .

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

0 115 11	
Certifications	III lietad tila E2875
Octilications	OL listed file L2075

Ordering and shipping details

Category	00117 - H&HU SW,VIEW WINDOW(VW)
Discount Schedule	DE1
Nbr. of units in pkg.	1
Package weight(Lbs)	42.9 lb(US) (19.46 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months