Product data sheet Characteristics


H322NRBVW

Safety switch, heavy duty, fusible, 60A, 3 poles, 15 hp, 240 VAC/250 VDC, NEMA 3R, bolt-on hub, neutral, viewing window





Price*: 929.00 USD



Main

	7
Single Throw Safety Switch	
Heavy duty	-
Heavy application	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Fusible disconnect	<u> </u>
Neutral (factory installed)	
3 phase	
3	
60 A	
250 V DC 240 V AC	for default
NEMA 3R galvannealed steel	- 0
3 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 7.5 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 10 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 430.52 15 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 10 hp 250 V at DC	of near or is not to a
	Heavy duty Heavy application Fusible disconnect Neutral (factory installed) 3 phase 3 60 A 250 V DC 240 V AC NEMA 3R galvannealed steel 3 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 7.5 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 10 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 10 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 15 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52

Complementary

Mounting Type	Surface	7
Wiring configuration	4-wire (3PH + G)	
Wire Size	AWG 14AWG 3 copper AWG 12AWG 3 aluminium	
Tightening torque	50 lbf.in (5.65 N.m) (AWG 3) 45 lbf.in (5.08 N.m) (AWG 6AWG 4) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 50 lbf.in (5.65 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)	is documentation
Depth	4.96 in (125.98 mm)	<u>-</u>

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	6.63 in (168.40 mm)
Height	14.6 in (370.84 mm)
Net Weight	9.57 lb(US) (4.34 kg)

Environment

Certifications	UL listed file E2875

Ordering and shipping details

Category	00117-H&HU SW,VIEW WINDOW(VW)
Discount Schedule	DE1
Package weight(Lbs)	8.60 lb(US) (3.901 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
PVC free	Yes

Contractual warranty

Warranty 18 months
