

Product data sheet

Characteristics

LDL34400WU44X

Circuit breaker, PowerPact L, unit mount,
Micrologic 6.3A, 400A, 3 pole, 18 kA, 480 VAC,
80% rated, mission critical



Main

Range of product	PowerPact L
Product or component type	Circuit breaker
Trip Unit Type	Electronic, ammeter, Micrologic 6.3 A-W, LSIG
Interrupt Code	D

Complementary

Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	25 kA 240 V AC 18 kA 480 V AC
Voltage Rating	480 V AC
Continuous current rating	80 %
Protection technology	Current limiter
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Size	AWG 2/0...500 kcmil aluminium/copper)2
Terminal Type	AL600LS52K3
Height	11.3 in (287.02 mm)
Width	5.5 in (139.70 mm)
Depth	6.61 in (167.89 mm)
Tightening torque	442.54 lbf.in (50 N.m) 0.11...0.37 in ² (70...240 mm ²) (AWG 2/0...500 kcmil)

Environment

Product certifications	CSA 22-2 CCC
------------------------	-----------------

IEC
CE
UL 489
NMX
NEMA

Ordering and shipping details

Category	01116-L ELEC TRIP UNIT MOUNT BREAKER/SW
Discount Schedule	DE2
Package weight(Lbs)	15.00 lb(US) (6.804 kg)
Returnability	Yes
Country of origin	US

Contractual warranty

Warranty	18 months
----------	-----------