Product data sheet Characteristics

H361DSWA

Safety switch, heavy duty, fusible, 30A, 600 VAC/ VDC, 3 poles, 20 hp, NEMA Type 4, 4X, 5, 304 steel, appleton receptacle

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 4,401.00 USD



Main

IVIAIII		
Product	Receptacle Switch	
For Use With	Plug ACP3034BC Appleton Powertite	
Disconnect Type	Fusible disconnect switch	
Phase	3 phase	
Number of Poles	3	
Current rating	30 A	
Voltage Rating	600 V AC 250 V DC	
Enclosure Rating NEMA 3R	NEMA 4/4X/5 stainless steel 304	
Maximum Horse Power Rating	5 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 15 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 7.5 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 20 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 5 hp 250 V at DC conforming to NEC 240.6	
	· · ·	

Complementary

Complementary	
Short-circuit Current Rating	10 kA H or K 200 kA R or J
Fuse Type	H or K R or J
Mounting Type	Surface
Electrical Connection	Receptacle
Wire Configuration	4-wire
Wire Size	AWG 12AWG 2 aluminium AWG 14AWG 2 copper
Tightening torque	45 lbf.in (5.08 N.m) (AWG 6)

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

40 lbf.in (4.52 N.m) (AWG 8)	
35 lbf in (3.95 N m) (AWG 14	AWG 10)

Depth	5.11 in (129.79 mm)
Width	10.81 in (274.57 mm)
Height	16.87 in (428.50 mm)
Net Weight	30.86 lb(US) (14 kg)

Environment

Certifications	UL Listed	
----------------	-----------	--

Ordering and shipping details

0 FF	
Category	00124 - H&HU SW,W/APPLETON RECPT - WA
Discount Schedule	DE1
GTIN	03606481243836
Nbr. of units in pkg.	1
Package weight(Lbs)	13 lb(US) (5.90 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	31.44 in (79.849 cm)
Package 1 width	7.37 in (18.732 cm)
Package 1 Length	13.44 in (34.129 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

Contractual warranty

Warranty	18 months
----------	-----------