Product data sheet Characteristics

H361NRBGL

Safety switch, heavy duty, fusible, 30A, 3 poles, 20 hp, 600 VAC/DC, NEMA 3R, bolt-on, neutral, equipment ground lugs





Price*: 665.00 USD



Main

Man		
Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	
Device application	Heavy application	
Disconnect Type	Fusible disconnect	
Factory Installed Neutral	Neutral (factory installed)	
Phase	3 phase	:
Number of Poles	3	
Current Rating	30 A	
Voltage Rating	600 V AC/DC	
Enclosure Rating	NEMA 3R galvannealed steel	
Maximum Horse Power Rating	5 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 15 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 7.5 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 20 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 15 hp 600 V at DC	

Complementary

Main		
Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	
Device application	Heavy application	
Disconnect Type	Fusible disconnect	
Factory Installed Neutral	Neutral (factory installed)	
Phase	3 phase	
Number of Poles	3	
Current Rating	30 A	
Voltage Rating	600 V AC/DC	
Enclosure Rating	NEMA 3R galvannealed steel	
Maximum Horse Power Rating	5 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 15 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 7.5 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 20 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 15 hp 600 V at DC	
Complementary		
Mounting Type	Surface	
Wiring configuration	4-wire (3PH + N)	
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper	
Tightening torque	45 lbf.in (5.08 N.m) 0.02 in² (13.3 mm²) (AWG 6) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 35 lbf.in (3.95 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)	
Depth	4.86 in (123.44 mm)	
Width	7.55 in (191.77 mm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	14.88 in (377.95 mm)
Environment	
Certifications	UL listed file E2875
Ordering and shipping details	
Category	00009-H&HU, 2&3P, N3R,30-200A
Discount Schedule	DE1
GTIN	00785901839484
Nbr. of units in pkg.	1
Package weight(Lbs)	8.80 lb(US) (3.992 kg)
Returnability	No
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	15.62 in (39.687 cm)
Package 1 width	5.00 in (12.7 cm)
Package 1 Length	7.50 in (19.05 cm)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

oontractaar marranty	
Warranty	18 months