Product data sheet Characteristics

H365AWKEI2

Safety switch, heavy duty, fusible, 400A, 3 poles, 250 hp, 600 VAC/DC, NEMA 12, interlock kit

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 6,135.00 USD



Main

iviairi		
Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	
Device application	Heavy application	
Disconnect Type	Fusible disconnect	
Factory Installed Neutral	None	
Phase	3 phase	
Number of Poles	3	
Current Rating	400 A	
Voltage Rating	600 V AC/DC	
Enclosure Rating	NEMA 3R/12	
Maximum Horse Power Rating	100 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 250 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 125 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 350 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 250 V at DC 50 hp 600 V at DC	

Complementary

Mounting Type	Surface	
Wiring configuration	3-wire	
Wire Size	AWG 1/0750 kcmil copper or aluminium	
Tightening torque	550 lbf.in (62.14 N.m) (AWG 1/0750 kcmil)	
Depth	10.13 in (257.30 mm)	
Width	26.25 in (666.75 mm)	
Height	46.25 in (1174.75 mm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

0 115 11	
Certifications	III lietad tila E2875
Octilications	OL listed file L2075

Ordering and shipping details

00155 - H&HU SW,NEMA12,400-1200A		
DE1		
00785901933144		
1		
175.00 lb(US) (79.379 kg)		
No		
MX		

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	46.26 in (117.5 cm)
Package 1 width	26.26 in (66.7 cm)
Package 1 Length	10.12 in (25.7 cm)

Offer Sustainability

Sustainable offer status	Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the St of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Compliant EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.		
Environmental Disclosure	Product Environmental Profile		
PVC free	Yes		
Halogen content performance	Halogen free plastic parts product		

Contractual warranty

Warranty	18 months	