

HRL36150M38X

Motor circuit protector, PowerPacT H, unit mount, 150A, 3 pole, 100 kA, 600 VAC, 80% rated



Main

Product or component type	Motor Circuit Protector
Range of product	PowerPact H
Trip Unit Type	Electronic, standard,
Breaking capacity code	R

Complementary

Line Rated Current	150 A
Number of Poles	3P
Interrupt Rating	200 kA 240 V AC 200 kA 480 V AC 100 kA 600 V AC
[Ue] rated operational voltage	600 V AC
Continuous current rating	80 %
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 14...AWG 3/0 aluminium/copper
Magnetic hold current	500 A
Magnetic tripping current	1300 A
Height	6.4 in (162.56 mm)
Width	4.12 in (104.65 mm)
Depth	4.36 in (110.74 mm)

Environment

Product certifications	IEC CCC CE CSA
------------------------	-------------------------

UL Listed

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	01108-H/J HIGH INTERRUPT UNIT MT CB/SW
Discount Schedule	DE2
Package weight(Lbs)	5.00 lb(US) (2.268 kg)
Returnability	Yes
Country of origin	US
