Product data sheet Characteristics

H365AWKGL


Safety switch, heavy duty, fusible, 400A, 3 poles, 250 hp, 600 VAC/DC, NEMA 12, equipment ground lugs

Product availability: Non-Stock - Not normally stocked in distribution facility

SQUARE 1



Price*: 5,517.00 USD



Main

Single Throw Safety Switch	
Heavy duty	
Heavy application	
Fusible disconnect	
None	
3 phase	
3	
400 A	
600 V AC/DC	
NEMA 3R/12	
100 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 250 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 125 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 350 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 250 V at DC 50 hp 600 V at DC	
	Heavy duty Heavy application Fusible disconnect None 3 phase 3 400 A 600 V AC/DC NEMA 3R/12 100 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 250 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 125 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 350 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 350 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 350 hp 250 V at DC

Complementary

Complementary		
Mounting Type	Surface	
Wiring configuration	3-wire	
Wire Size	AWG 1/0750 kcmil copper or aluminium	
Tightening torque	550 lbf.in (62.14 N.m) (AWG 1/0750 kcmil)	
Depth	10.13 in (257.30 mm)	
Width	26.25 in (666.75 mm)	
Height	46.25 in (1174.75 mm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Certifications	UL listed file E2875

Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A	
Discount Schedule	DE1	
GTIN	00785901486817	
Nbr. of units in pkg.	1	
Package weight(Lbs)	175 lb(US) (79.38 kg)	
Returnability	No	
Country of origin	MX	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, is known to the State of California to cause cancer and birth defects or other reproductive ha more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	

Contractual warranty

	· · · · · · · · · · · · · · · · · · ·	
Warranty	18 months	