

Product data sheet

Characteristics

QO1520CP

Tandem mini circuit breaker, QO, 1 x 1 pole at 15A, 1 x 1 pole at 20A, 120/240 VAC, 10 kA, plug in mount, consumer pack

Product availability : Stock - Normally stocked in distribution facility



Price* : 41.90 USD



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	15 A 20 A
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Tandem
Ratings	HACR rated
Electrical Connection	Box lugs
Type of Packing	Consumer packaging

Complementary

Interrupt Rating	10 kA 120/240 V AC 50/60 Hz
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper or aluminium
Tightening Torque	44.25 lbf.in (5 N.m) 0.02...0.04 in ² (10...25 mm ²) (AWG 8...AWG 2)
Height	3.22 in (81.79 mm)
Width	0.75 in (19.05 mm)
Depth	2.91 in (73.91 mm)

Environment

Certifications	UL Listed CSA
----------------	------------------

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

Ambient Rating	104 °F (40 °C)
----------------	----------------

Ordering and shipping details

Category	01329 - QO TANDEMS BULK BRKRS.
Discount Schedule	CPQ
GTIN	00047569044113
Nbr. of units in pkg.	1
Package weight(Lbs)	4.96 oz (140.614 g)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.70 in (1.778 cm)
Package 1 width	3.20 in (8.128 cm)
Package 1 Length	2.90 in (7.366 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Halogen content performance	Halogen free product