



Main

Range	TeSys
Product name	TeSys LK
Product or component type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch
Suitability for isolation	Yes

Complementary

Poles description	3P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	630 A690 V AC AC-22A IEC 400 A690 V AC AC-23A IEC 1000 A400 V AC AC-22A IEC 1000 A400 V AC AC-23A IEC 1000 A CSA 1000 A UL
[Ue] rated operational voltage	600 V AC 50/60 Hz
[Ui] rated insulation voltage	1000 V
Control type	Rotary handle
Type of operating handle	External right side External frontal
Mounting support	Plate
[Uimp] rated impulse withstand voltage	12 kV IEC
Rated power in W	560 kW 500 V 400 kW 690 V 560 kW 400 V
Rated power in hp	200 hp 240 V 480 A AC 500 hp 480 V 590 A AC 500 hp 600 V 472 A AC
[Icw] rated short-time withstand current	75 kA
Mechanical durability	3500 cycles
Electrical durability	500 cycles
Connections - terminals	lugs-ring terminals 2 0.05 in ² (34 mm ²)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

	bars 2 50 x 5 mm
Height	12.60 in (320 mm)
Width	14.57 in (370 mm)
Depth	5.51 in (140 mm)

Environment

Standards	CSA C22.2 No 4 UL98 IEC 60947-3
Product certifications	UL CE CSA

Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	00785901546955
Nbr. of units in pkg.	1
Package weight(Lbs)	20.06 lb(US) (9.1 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.63 in (27 cm)
Package 1 width	15.94 in (40.5 cm)
Package 1 Length	20.87 in (53 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------