# Product data sheet Characteristics

# HU363DSEI2

Safety switch, heavy duty, non fusible, 100A, 3 poles, 100 hp, 600 VAC/DC, NEMA 4, 4X, 5, 304 steel, interlock kit

Product availability: Non-Stock - Not normally stocked in distribution facility

SQUARE D



Price\*: 5,604.00 USD



### Main

Main		
Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	
Device application	Heavy application	
Disconnect Type	Non-fusible disconnect	
Factory Installed Neutral	None	
Phase	3 phase	
Number of Poles	3	
Current Rating	100 A	
Voltage Rating	600 V AC/DC	
Enclosure Rating	NEMA 4/4X/5 stainless steel 304	
Maximum Horse Power Rating	20 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 430.52 40 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 40 hp 480 V at AC 50-60 Hz for 1 phase conforming to NEC 430.52 75 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 40 hp 600 V at AC 50-60 Hz for 1 phase conforming to NEC 430.52 100 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 20 hp 250 V at DC 50 hp 600 V at DC	:

#### Complementary

o o p . o c		.=
Mounting Type	Surface	
Wiring configuration	3-wire	
Wire Size	AWG 12AWG 1/0 aluminium AWG 14AWG 1/0 copper	- Edman
Tightening torque	50 lbf.in (5.65 N.m) (AWG 1AWG 3/0) 45 lbf.in (5.08 N.m) (AWG 6AWG 4) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8)	iri Siri

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Depth	6.97 in (177.04 mm)
Width	11.25 in (285.75 mm)
Height	20.82 in (528.83 mm)

#### Environment

UL listed file E2875	
	UL listed file E2875

#### Ordering and shipping details

<u> 0   - 0   </u>	
Category	00010 - H&HU SW,2&3P,N4,SS,30-200A
Discount Schedule	DE1
GTIN	00785901494560
Nbr. of units in pkg.	1
Package weight(Lbs)	10 lb(US) (4.54 kg)
Returnability	No
Country of origin	US

#### **Packing Units**

Package 1 Height	7.60 in (19.304 cm)	
Package 1 width	11.70 in (29.718 cm)	
Package 1 Length	23.40 in (59.436 cm)	

## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

#### Contractual warranty

Contractada Warranty	
Warranty	18 months