Product data sheet Characteristics

9070T5000D6


Transformer, Type T, industrial control, 5000 VA, 380 VAC primary / 110 VAC secondary, 1 phase, 50/60 Hz, 115 °C rise

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 2,423.00 USD



Main

Product Type	Industrial Control Transformer
Power Rating	3000 VA 5000 VA
Туре	Т

Complementary

Power Rating 5000 VA UL 5000 VA CSA 5000 VA NOM 3000 VA Temperature Rise 115 °C Electrical Connection Screw clamp terminals Fingersafe Cover Compatibility FSC2 Environment Certifications UL Listed CSA Enclosure Type Not rated (open device) Insulation Temperature Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA			
Product Type Industrial Control Transformer Power Rating 3000 VA 5000 VA Type T Complementary Number of Phases 1 phase			
Product Type Industrial Control Transformer Power Rating 3000 VA 5000 VA Type T Complementary Number of Phases 1 phase Power Rating 5000 VA UL 5000 VA CSA 5000 VA NOM 3000 VA Temperature Rise 115 °C Electrical Connection Screw clamp terminals Fingersafe Cover Compatibility FSC2 Environment Certifications UL Listed CSA Enclosure Type Not rated (open device) Insulation Temperature 356 °F (180 °C) Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA			
Power Rating 3000 VA 5000 VA	Main		
Type	Product Type	Industrial Control Transformer	
Complementary Number of Phases 1 phase Power Rating 5000 VA UL 5000 VA CSA 5000 VA NOM 3000 VA Temperature Rise 115 °C Electrical Connection Screw clamp terminals Fingersafe Cover Compatibility FSC2 Environment Certifications UL Listed CSA Enclosure Type Not rated (open device) Insulation Temperature 356 °F (180 °C) Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Power Rating		
Number of Phases 1 phase Power Rating 5000 VA UL 5000 VA CSA 5000 VA NOM 3000 VA Temperature Rise 115 °C Electrical Connection Screw clamp terminals Fingersafe Cover Compatibility FSC2 Environment Certifications UL Listed CSA Enclosure Type Not rated (open device) Insulation Temperature 356 °F (180 °C) Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Туре	Т	
Power Rating 5000 VA UL 5000 VA CSA 5000 VA NOM 3000 VA Temperature Rise 115 °C Electrical Connection Screw clamp terminals Fingersafe Cover Compatibility FSC2 Environment Certifications UL Listed CSA Enclosure Type Not rated (open device) Insulation Temperature Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Complementary		
5000 VA CSA 5000 VA NOM 3000 VA Temperature Rise 115 °C Electrical Connection Screw clamp terminals Fingersafe Cover Compatibility FSC2 Environment Certifications UL Listed CSA Enclosure Type Not rated (open device) Insulation Temperature 356 °F (180 °C) Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Number of Phases	1 phase	
Electrical Connection Screw clamp terminals Fingersafe Cover Compatibility FSC2 Environment Certifications UL Listed CSA Enclosure Type Not rated (open device) Insulation Temperature 356 °F (180 °C) Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Power Rating	5000 VA CSA 5000 VA NOM	
Environment Certifications UL Listed CSA Enclosure Type Not rated (open device) Insulation Temperature Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Temperature Rise	115 °C	
Environment Certifications UL Listed CSA Enclosure Type Not rated (open device) Insulation Temperature 356 °F (180 °C) Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Electrical Connection	Screw clamp terminals	
Certifications UL Listed CSA Enclosure Type Not rated (open device) Insulation Temperature 356 °F (180 °C) Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Fingersafe Cover Compatibility	FSC2	
Certifications UL Listed CSA Enclosure Type Not rated (open device) Insulation Temperature 356 °F (180 °C) Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Environment		
Insulation Temperature 356 °F (180 °C) Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA			
Ordering and shipping details Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Enclosure Type	Not rated (open device)	
Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Insulation Temperature	356 °F (180 °C)	
Category 16205 - 9070 T (NOT TF) 3000 - 5000VA	Ordering and shipping detail	s	
	Discount Schedule	CP8	

Environment

		į
Certifications	UL Listed CSA	, , , , , , , , , , , , , , , , , , ,
Enclosure Type	Not rated (open device)	
Insulation Temperature	356 °F (180 °C)	9

Ordering and shipping details

ordoning and ompping dotain		
Category	16205 - 9070 T (NOT TF) 3000 - 5000VA	7
Discount Schedule	CP8	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Nbr. of units in pkg.	1	
Package weight(Lbs)	91.1 lb(US) (41.32 kg)	
Returnability	No	
Packing Units		
Package 1 Height	12.50 in (31.750 cm)	
Package 1 width	12.38 in (31.445 cm)	
Package 1 Length	12.38 in (31.445 cm)	
Offer Sustainability Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

18 months

Contractual warranty

Warranty