Product data sheet Characteristics

9070T750D17

Transformer, Type T, industrial control, 750 VA, 415 VAC primary / 110 VAC secondary, 1 phase, 50/60 Hz, 115 °C rise

Product availability: Non-Stock - Not normally stocked in distribution facility

SQUARE D



Price*: 783.00 USD



Main

Product Type	Industrial Control Transformer
Power Rating	750 VA 500 VA
Туре	Т

Complementary

Power Rating 7 Type 7 Complementary Number of Phases 1 Power Rating 7 Temperature Rise 1 Electrical Connection 5	Industrial Control Transformer 750 VA 750 VA 750 VA 750 VA UL 750 VA CSA 750 VA NOM 750 VA CSA
Product Type Power Rating 7 5 Type 1 Complementary Number of Phases 1 Power Rating 7 7 7 5 Temperature Rise Electrical Connection	750 VA 500 VA T I phase 750 VA UL 750 VA CSA 750 VA NOM 500 VA
Product Type In Power Rating 7 Type 1 Complementary Number of Phases 1 Power Rating 7 7 7 5 1 Temperature Rise 1 Electrical Connection 5	Industrial Control Transformer 750 VA 750 VA 750 VA T I phase 750 VA UL 750 VA CSA 750 VA NOM 750 VA NOM 750 VA Son VA 750 VA
Product Type II Power Rating 7 Type 1 Complementary Number of Phases 1 Power Rating 7 7 7 5 1 Temperature Rise 1 Electrical Connection 5	Industrial Control Transformer 750 VA 600 VA T I phase 750 VA UL 750 VA CSA 750 VA NOM 600 VA 115 °C Screw clamp terminals
Product Type In Power Rating 7 Type 1 Complementary Number of Phases 1 Power Rating 7 7 7 5 1 Temperature Rise 1 Electrical Connection 5	Industrial Control Transformer 750 VA 500 VA T I phase 750 VA UL 750 VA CSA 750 VA NOM 500 VA Ils °C Screw clamp terminals
Power Rating 5 Type 7 Complementary Number of Phases 1 Power Rating 7 Temperature Rise 1 Electrical Connection 5	750 VA 600 VA T I phase 750 VA UL 750 VA CSA 750 VA NOM 600 VA 115 °C Screw clamp terminals
Complementary Number of Phases 1 Power Rating 7 7 7 5 Temperature Rise 1 Electrical Connection S	phase 750 VA UL 750 VA CSA 750 VA NOM 500 VA 115 °C Screw clamp terminals
Number of Phases 1 Power Rating 7 7 7 5 Temperature Rise 1 Electrical Connection S	I phase 750 VA UL 750 VA CSA 750 VA NOM 600 VA
Number of Phases 1 Power Rating 7 7 7 5 Temperature Rise 1 Electrical Connection S	phase 750 VA UL 750 VA CSA 750 VA NOM 500 VA 115 °C Screw clamp terminals
Power Rating 7 7 7 7 8 Temperature Rise 1 Electrical Connection S	phase 750 VA UL 750 VA CSA 750 VA NOM 600 VA
Temperature Rise 1 Electrical Connection S	750 VA UL 750 VA CSA 750 VA NOM 500 VA 115 °C Grew clamp terminals
Temperature Rise 1 Electrical Connection 5	115 °C Screw clamp terminals
Electrical Connection S	
	screw clamp terminals
Fingersafe Cover Compatibility F	
	FSC2
Environment	
	JL Listed CSA
Enclosure Type	Not rated (open device)
Insulation Temperature 3	856 °F (180 °C)
Ordering and shipping details	
	6201 - 9070 T (NOT TF) 250-2000VA
	CP8

Environment

LITTION		i
Certifications	UL Listed CSA	
Enclosure Type	Not rated (open device)	
Insulation Temperature	356 °F (180 °C)	

Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Nbr. of units in pkg.	1
Package weight(Lbs)	17.2 lb(US) (7.80 kg)
Returnability	No
Country of origin	US

Packing Units

Package 1 Height	6.50 in (16.510 cm)
Package 1 width	8.50 in (21.590 cm)
Package 1 Length	8.00 in (20.320 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65 WARNING: This product can expose you to chemicals including: Phenyl glycidyl etl known to the State of California to cause cancer and birth defects or other reproduct more information go to www.P65Warnings.ca.gov		
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	ure Product Environmental Profile	
PVC free	Yes	

Contractual warranty

Warranty	18 months