Product data sheet Characteristics

NSYSF16880

Spacial SF enclosure without mounting plate - assembled - 1600x800x800 mm

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 1,422.85 USD



Main

| IVIAIII | |
|---------------------------|---|
| Range | Spacial |
| Extended range | Spacial SF |
| Application | Multi-purpose |
| Product or component type | Suitable enclosure |
| Enclosure nominal height | 62.99 in (1600 mm) |
| Enclosure nominal width | 31.50 in (800 mm) |
| Enclosure nominal depth | 31.50 in (800 mm) |
| Enclosure mounting | Floor-standing |
| Device composition | 2 sliding rails 4 mounting plate bracket 1 structure 1 door 1 locking system with handle door 1 rear panel 1 roof |

Complementary

| Complementary | | |
|-----------------------------|---|---|
| Structure type | Panels and doors built into the structure Vertical uprights joined with top and bottom frames Formed from a single section Perforated structure with a pitch of 25 mm | |
| Door type | Solid front | |
| Number of doors | Front 1 | } |
| Door opening side | Reversible 120 °) | |
| Lock type | 4 points lock, handle with 5 mm double bar insert front door | *************************************** |
| Mounting plate description | Without mounting plate | |
| Type of gland plate | Without gland plate | |
| Accessibility for operation | Front | |

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | Sides of enclosure Rear |
|-----------------|---|
| Removable parts | Door by screws hinge Rear panel by screws Roof by screws Mounting plate bracket by screws Sliding rail by screws |
| Material | Frame galvanised steel Uprights galvanised steel Door sheet steel Panels sheet steel Hinge zamak Handle polyamide 6 with 30 % fibre glass |
| Surface finish | epoxy-polyester powder |
| Color | Enclosure Gray RAL 7035) Handle Black RAL 9005) |
| Net Weight | 292.11 lb(US) (132.5 kg) |

Environment

| Standards | IEC 62208 |
|-------------------------|------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK10 IEC 62262 |

Ordering and shipping details

| 80035 - ENCLOSURE SYSTEMS FLOOR MOUNT |
|---------------------------------------|
| ES1 |
| 03606485118024 |
| 1 |
| 292.11 lb(US) (132.5 kg) |
| No |
| ES |
| |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------|--------------------|--|
| Package 1 Height | 68.11 in (173 cm) | |
| Package 1 width | 33.27 in (84.5 cm) | |
| Package 1 Length | 35.04 in (89 cm) | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| | |

Contractual warranty

| Warranty | 18 months | |
|----------|-----------|--|