Product data sheet Characteristics

LLP36400U33XAB

Circuit breaker, PowerPact L, unit mount, Micrologic 3.3S, 400A, 3 pole, 50 kA, 600 VAC, 80% rated, auxiliary switch

Product availability: Non-Stock - Not normally stocked in distribution facility

SQUARE D





Main

D 1 1	
Product or component type	Circuit breaker

Complementary

C C p . C		
Number of Poles	3P	
Breaking capacity code	L	
Electrical connection	Terminal nut line Lugs load	
Terminal identifier	AL600LS52K3	
Tightening torque	442.54 lbf.in (50 N.m) 0.110.37 in² (70240 mm²) (AWG 2/0500 kcmil)	
Height	11.3 in (287.02 mm)	
Width	5.5 in (139.70 mm)	
Depth	6.61 in (167.89 mm)	
Continuous current rating	80 %	

Ordering and shipping details

01116 - L ELEC TRIP UNIT MOUNT BREAKER/SW	
DE2	
1	
15 lb(US) (6.80 kg)	
No	
US	
	DE2 1 15 lb(US) (6.80 kg) No

Offer Sustainability

Sustainable offer status Green Premium product			
	Sustainable offer status	Green Premium product	

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free Yes		
RoHS exemption information	on Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
VC free Yes		

Contractual warranty

Warranty	18 months