


# LP1D80008BD

IEC contactor, TeSys D, nonreversing, 125A resistive, 4 pole, 2 NO and 2 NC, 24VDC coil, open style

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 599.00 USD



## Main

|                                             |                                                                                                                                                                                    |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                       | TeSys                                                                                                                                                                              |
| Product name                                | TeSys D                                                                                                                                                                            |
| Product or component type                   | Contactor                                                                                                                                                                          |
| Device short name                           | LP1D                                                                                                                                                                               |
| Contactor application                       | Resistive load                                                                                                                                                                     |
| Utilisation category                        | AC-1                                                                                                                                                                               |
| Poles description                           | 4P                                                                                                                                                                                 |
| Power pole contact composition              | 2 NO + 2 NC                                                                                                                                                                        |
| [Ue] rated operational voltage              | Power circuit: $\leq 1000$ V AC 25...400 Hz<br>Power circuit $\leq 300$ V DC                                                                                                       |
| [Ie] rated operational current              | 125 A 140 °F (60 °C) $\leq 440$ V AC AC-1 power circuit                                                                                                                            |
| [Uc] control circuit voltage                | 24 V DC                                                                                                                                                                            |
| Coil type                                   | DC standard                                                                                                                                                                        |
| [Uimp] rated impulse withstand voltage      | 8 kV IEC 60947                                                                                                                                                                     |
| Overvoltage category                        | III                                                                                                                                                                                |
| [Ith] conventional free air thermal current | 125 A 140 °F (60 °C) power circuit                                                                                                                                                 |
| Irms rated making capacity                  | 1100 A 440 V power circuit IEC 60947                                                                                                                                               |
| Rated breaking capacity                     | 1100 A 440 V power circuit IEC 60947                                                                                                                                               |
| [Icw] rated short-time withstand current    | 135 A 104 °F (40 °C) - 10 min power circuit<br>320 A 104 °F (40 °C) - 1 min power circuit<br>640 A 104 °F (40 °C) - 10 s power circuit<br>990 A 104 °F (40 °C) - 1 s power circuit |
| Associated fuse rating                      | 200 A gG $\leq 690$ V type 1 power circuit<br>160 A gG $\leq 690$ V type 2 power circuit                                                                                           |
| Average impedance                           | 0.8 mOhm - Ith 125 A 50 Hz power circuit                                                                                                                                           |

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage | Power circuit 600 V CSA<br>Power circuit 600 V UL<br>Power circuit 1000 V IEC 60947-4-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Electrical durability         | 0.8 Mcycles 125 A AC-1 ≤ 440 V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Power dissipation per pole    | 12.5 W AC-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Front cover                   | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Mounting support              | Plate<br>Rail                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Standards                     | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Product certifications        | BV<br>CCC<br>CSA<br>DNV<br>EAC<br>GL<br>LROS (Lloyds register of shipping)<br>UL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Connections - terminals       | Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible without cable end<br>Control circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible without cable end<br>Control circuit screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible with cable end<br>Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid<br>Control circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid<br>Power circuit connector 1 0.01...0.08 in <sup>2</sup> (4...50 mm <sup>2</sup> )flexible without cable end<br>Power circuit connector 2 0.01...0.04 in <sup>2</sup> (4...25 mm <sup>2</sup> )flexible without cable end<br>Power circuit connector 1 0.01...0.08 in <sup>2</sup> (4...50 mm <sup>2</sup> )flexible with cable end<br>Power circuit connector 2 0.01...0.02 in <sup>2</sup> (4...16 mm <sup>2</sup> )flexible with cable end<br>Power circuit connector 1 0.01...0.08 in <sup>2</sup> (4...50 mm <sup>2</sup> )solid<br>Power circuit connector 2 0.01...0.04 in <sup>2</sup> (4...25 mm <sup>2</sup> )solid<br>Control circuit screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible with cable end |
| Tightening torque             | Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals flat Ø 6 mm<br>Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals Philips No 2<br>Power circuit 106.21 lbf.in (12 N.m) connector flat Ø 6 to Ø 8 mm<br>Power circuit 106.21 lbf.in (12 N.m) connector hexagonal 0.16 in (4 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Operating time                | 6...20 ms opening<br>20...35 ms closing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Safety reliability level      | B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Mechanical durability         | 4 Mcycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Maximum operating rate        | 3600 cyc/h 140 °F (60 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

## Complementary

|                                |                                                                                                                                                                       |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Coil technology                | Without built-in suppressor module                                                                                                                                    |
| Control circuit voltage limits | 0.1...0.3 Uc -40...158 °F (-40...70 °C) drop-out DC<br>0.85...1.1 Uc -40...131 °F (-40...55 °C) operational DC<br>1...1.1 Uc 131...158 °F (55...70 °C) operational DC |
| Time constant                  | 75 ms                                                                                                                                                                 |
| Inrush power in W              | 22 W 68 °F (20 °C)                                                                                                                                                    |
| Hold-in power consumption in W | 22 W 68 °F (20 °C)                                                                                                                                                    |

## Environment

|                                       |                                                                       |
|---------------------------------------|-----------------------------------------------------------------------|
| IP degree of protection               | IP20 front face IEC 60529                                             |
| Protective treatment                  | TH IEC 60068-2-30                                                     |
| Pollution degree                      | 3                                                                     |
| Ambient air temperature for operation | -40...140 °F (-40...60 °C)<br>140...158 °F (60...70 °C) with derating |
| Ambient air temperature for storage   | -76...176 °F (-60...80 °C)                                            |
| Operating altitude                    | 0...9842.52 ft (0...3000 m)                                           |

|                       |                                                                                                                                                                             |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire resistance       | 1562 °F (850 °C) IEC 60695-2-1                                                                                                                                              |
| Flame retardance      | V1 conforming to UL 94                                                                                                                                                      |
| Mechanical robustness | Vibrations contactor open2 Gn, 5...300 Hz<br>Vibrations contactor closed: 3 Gn, 5...300 Hz<br>Shocks contactor open8 Gn for 11 ms<br>Shocks contactor closed10 Gn for 11 ms |
| Height                | 5.00 in (127 mm)                                                                                                                                                            |
| Width                 | 3.78 in (96 mm)                                                                                                                                                             |
| Depth                 | 7.72 in (196 mm)                                                                                                                                                            |
| Net Weight            | 6.42 lb(US) (2.91 kg)                                                                                                                                                       |

### Ordering and shipping details

|                       |                                           |
|-----------------------|-------------------------------------------|
| Category              | 22359 - CTR, TESYS D, OPEN, 80-150A AC&DC |
| Discount Schedule     | I12                                       |
| GTIN                  | 03389110234329                            |
| Nbr. of units in pkg. | 1                                         |
| Package weight(Lbs)   | 6.51 lb(US) (2.955 kg)                    |
| Returnability         | No                                        |
| Country of origin     | CZ                                        |

### Packing Units

|                        |                   |
|------------------------|-------------------|
| Unit Type of Package 1 | PCE               |
| Package 1 Height       | 8.86 in (22.5 cm) |
| Package 1 width        | 5.83 in (14.8 cm) |
| Package 1 Length       | 7.09 in (18 cm)   |

### Offer Sustainability

|                            |                                                                                                                                                                                                                                                           |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                     |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                         |
| REACH free of SVHC         | Yes                                                                                                                                                                                                                                                       |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                          |
| Toxic heavy metal free     | Yes                                                                                                                                                                                                                                                       |
| Mercury free               | Yes                                                                                                                                                                                                                                                       |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                       |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                                                                                                                                               |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                             |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                              |
| PVC free                   | Yes                                                                                                                                                                                                                                                       |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|