# Product data sheet Characteristics

## HU662AWKVW


Safety switch, heavy duty, non fusible, 60A, 6 poles, 60 hp, 600 VAC/DC, NEMA 12, viewing window

Product availability: Non-Stock - Not normally stocked in distribution facility





Price\*: 3,959.00 USD



#### Main

Man	
Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	6
Current Rating	60 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 3R/12
Maximum Horse Power Rating	20 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 60 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52

### Complementary

Wiring configuration         6-wire           Wire Size         AWG 14AWG 3 copper AWG 12AWG 3 aluminium           Tightening torque         50 lbf.in (5.65 N.m) (AWG 3) 45 lbf.in (5.08 N.m) (AWG 6AWG 4) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 50 lbf.in (5.65 N.m) 0.0001 in² (2.065.261 mm²) (AWG 14AWG 10)           Depth         6.8 in (172.72 mm)           Width         16 13 in (409.70 mm)	Mounting Type	Surface	
AWG 12AWG 3 aluminium  Tightening torque  50 lbf.in (5.65 N.m) (AWG 3) 45 lbf.in (5.08 N.m) (AWG 6AWG 4) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 50 lbf.in (5.65 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)  Depth  6.8 in (172.72 mm)	Wiring configuration	6-wire	
45 lbf.in (5.08 N.m) (AWG 6AWG 4) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 50 lbf.in (5.65 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)  Depth 6.8 in (172.72 mm)	Wire Size	• • • • • • • • • • • • • • • • • • • •	
· · · · · · · · · · · · · · · · · · ·	Tightening torque	45 lbf.in (5.08 N.m) (AWG 6AWG 4) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8)	
Width 16.13 in (409.70 mm)	Depth	6.8 in (172.72 mm)	
width 10.10 in (403.70 fillin)	Width	16.13 in (409.70 mm)	

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	20.5 in (520.70 mm)
Environment	
Certifications	UL listed file E2875
Corumodionio	OF HOLDS THE FEOTO
Ordering and shipping details	
Category	00116 - H&HU SW,4&6P,N12,30-200A
Discount Schedule	DE1
GTIN	00785901675839
Nbr. of units in pkg.	1
Package weight(Lbs)	10.00 lb(US) (4.536 kg)
Returnability	No
Country of origin	US
Packing Units Unit Type of Package 1 Package 1 Height	PCE 20.51 in (52.1 cm)
Package 1 Height	20.51 in (52.1 cm)
Package 1 width	16.14 in (41 cm)
Package 1 Length	6.81 in (17.3 cm)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Diselecture	Draduct Engineering Drafile

#### Contractual warranty

Environmental Disclosure

PVC free

Contractual warranty	ontractidal warranty		
Warranty	18 months		

Product Environmental Profile

Yes