Product data sheet Characteristics

QO318L200I

Load center interior, QO, 3 phase, 18 spaces, 18 circuits, 200A fixed main lugs, NEMA1, UL

SQUARE D

Price*: 426.00 USD



Main

Main		4
Product Type	Load Center Interior	- 4017
Marketing Trade Name	QO	- Dro
Load Center Type	Main lugs	these
Rated Current	200 A	itv of
Number of Spaces	18	eliability
Max Short Circuit Current Rating	65 kA	- 20
Maximum Number of Single Pole Circuits	18	Suitabilit
Maximum Number of Tandem Breakers	0	ermining
Number of Phases	3 phase	- det
Voltage Rating	208Y/120 V AC 240/120 V delta AC 240 V delta AC	to be used for

Complementary

Ground Bar	Grounding bar (ordered separately)	ute f
Busbar Material	Tin plated copper busbar	ubsti
Product Certifications	UL Listed	് മ
Tightening Torque	28 N.m, AWG 4250 kcmil	

Environment

	22 % (5 % C)	
Ambient Air Temperature for	23 °F (-5 °C)	
/ in bicht / in Temperature for	20 1 (0 0)	
O	404 °F (40 °C)	
Operation	104 °F (40 °C)	
- 1	- (/	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	00199-DE5 MISC. SERVICE PARTS
Discount Schedule	DE5
Package weight(Lbs)	10.00 lb(US) (4.536 kg)
Returnability	No

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

Contractual warranty

	,		
Warranty	18	months	