

Product data sheet

Characteristics

QO342L225I

Load center interior, QO, 3 phase, 42 spaces, 42 circuits, 225A fixed main lugs, NEMA1, UL



Price* : 809.00 USD



Main

Product Type	Load Center Interior
Marketing Trade Name	QO
Load Center Type	Main lugs
Rated Current	225 A
Number of Spaces	42
Max Short Circuit Current Rating	65 kA
Maximum Number of Single Pole Circuits	42
Maximum Number of Tandem Breakers	0
Number of Phases	3 phase
Voltage Rating	208Y/120 V AC 240/120 V delta AC 240 V delta AC

Complementary

Ground Bar	Grounding bar (ordered separately)
Busbar Material	Tin plated copper busbar
Product Certifications	UL Listed
Tightening Torque	28 N.m, AWG 4...300 kcmil

Environment

Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
---------------------------------------	---------------------------------

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

Ordering and shipping details

Category	00199-DE5 MISC. SERVICE PARTS
Discount Schedule	DE5
Package weight(Lbs)	10.00 lb(US) (4.536 kg)
Returnability	No

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

Contractual warranty

Warranty	18 months
----------	-----------