

## Product data sheet

### Characteristics


# NSYTBS191210HT

ABS box IP66 IK07 RAL7035 Int.H175W105D100  
Ext.H192W121D105 Transp.cover H40

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 44.06 USD



### Main

|                     |                                        |
|---------------------|----------------------------------------|
| Range               | Thalassa                               |
| Product name        | Thalassa TBS                           |
| Device application  | Multi-purpose                          |
| Category            | Industrial box                         |
| Height              | 7.56 in (192 mm)                       |
| Width               | 4.76 in (121 mm)                       |
| Depth               | 4.13 in (105 mm)                       |
| Internal height     | 6.89 in (175 mm)                       |
| Internal width      | 4.13 in (105 mm)                       |
| Internal depth      | 3.94 in (100 mm)                       |
| Enclosure mounting  | Wall mounted                           |
| Device composition  | 1 body<br>1 cover<br>4 cover screw     |
| Quantity per set    | Set of 2                               |
| Body type           | One piece moulded                      |
| Type of front cover | High transparent cover                 |
| Cover fixing        | Plastic screws                         |
| Lock type           | Captive screw flat outside sealed area |
| Removable parts     | Cover by captive screws                |

### Complementary

|           |                                       |
|-----------|---------------------------------------|
| Material  | ABS (acrylonitrile butadiene-styrene) |
| Color     | Gray RAL 7035)<br>Transparent         |
| Standards | IEC 62208                             |

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

|                                     |                                 |
|-------------------------------------|---------------------------------|
| Product certifications              | TÜV                             |
| Electrical insulation class         | Class II                        |
| IP degree of protection             | IP66 conforming to NEMA 4.4X    |
| IK degree of protection             | IK07 conforming to IEC 62262    |
| Glow wire resistance                | 1202 °F (650 °C) IEC 60695-2-11 |
| Ambient air temperature for storage | 5...104 °F (-15...40 °C)        |
| Operating temperature               | -13...140 °F (-25...60 °C)      |
| Net Weight                          | 0.99 lb(US) (0.45 kg)           |

### Ordering and shipping details

|                       |                                     |
|-----------------------|-------------------------------------|
| Category              | 80033 - ENCLOSURE SYSTEMS POLYESTER |
| Discount Schedule     | ES1                                 |
| GTIN                  | 03606480165450                      |
| Nbr. of units in pkg. | 1                                   |
| Package weight(Lbs)   | 15.87 oz (450 g)                    |
| Returnability         | No                                  |
| Country of origin     | HU                                  |

### Packing Units

|                        |                  |
|------------------------|------------------|
| Unit Type of Package 1 | PCE              |
| Package 1 Height       | 4.72 in (12 cm)  |
| Package 1 width        | 7.87 in (20 cm)  |
| Package 1 Length       | 10.24 in (26 cm) |

### Offer Sustainability

|                            |                                                                                                             |
|----------------------------|-------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                           |
| REACH free of SVHC         | Yes                                                                                                         |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>           |
| Toxic heavy metal free     | Yes                                                                                                         |
| Mercury free               | Yes                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|