

# Product data sheet

## Characteristics

# NSYTBP29248

PC box IP66 IK08 RAL7035 Int.H275W225D80  
Ext.H291W241D88 opaque PC cover H20

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 101.53 USD



### Main

|                     |  |
|---------------------|--|
| Range               | Thalassa                               |
| Product name        | Thalassa TBP                           |
| Device application  | Multi-purpose                          |
| Category            | Industrial box                         |
| Height              | 11.46 in (291 mm)                      |
| Width               | 9.49 in (241 mm)                       |
| Depth               | 3.46 in (88 mm)                        |
| Internal height     | 10.83 in (275 mm)                      |
| Internal width      | 8.86 in (225 mm)                       |
| Internal depth      | 3.15 in (80 mm)                        |
| Enclosure mounting  | Wall mounted                           |
| Device composition  | 1 body<br>1 cover<br>4 cover screw     |
| Body type           | One piece moulded                      |
| Type of front cover | Low plain cover                        |
| Cover fixing        | Plastic screws                         |
| Lock type           | Captive screw flat outside sealed area |
| Removable parts     | Cover by captive screws                |

### Complementary

|                        |                       |
|------------------------|-----------------------|
| Material               | polycarbonate         |
| Color                  | Gray RAL 7035)        |
| Standards              | UL 508 A<br>IEC 62208 |
| Product certifications | TÜV                   |

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

UL

|                             |                       |
|-----------------------------|-----------------------|
| Electrical insulation class | Class II              |
| Mounting location           | Outdoor               |
| Net Weight                  | 1.90 lb(US) (0.86 kg) |

## Environment

|                                     |                              |
|-------------------------------------|------------------------------|
| IP degree of protection             | IP66 conforming to NEMA 4.4X |
| IK degree of protection             | IK08 conforming to IEC 62262 |
| Fire resistance                     | 1760 °F (960 °C)             |
| Ambient air temperature for storage | 5...140 °F (-15...60 °C)     |
| Operating temperature               | -13...176 °F (-25...80 °C)   |

## Ordering and shipping details

|                       |                                     |
|-----------------------|-------------------------------------|
| Category              | 80033 - ENCLOSURE SYSTEMS POLYESTER |
| Discount Schedule     | ES1                                 |
| GTIN                  | 03606480165726                      |
| Nbr. of units in pkg. | 1                                   |
| Package weight(Lbs)   | 33.93 oz (962 g)                    |
| Returnability         | No                                  |
| Country of origin     | HU                                  |

## Packing Units

|                              |                           |
|------------------------------|---------------------------|
| Unit Type of Package 1       | PCE                       |
| Package 1 Height             | 3.94 in (10 cm)           |
| Package 1 width              | 9.84 in (25 cm)           |
| Package 1 Length             | 12.01 in (30.5 cm)        |
| Unit Type of Package 2       | S04                       |
| Number of Units in Package 2 | 8                         |
| Package 2 Weight             | 18.36 lb(US) (8.329 kg)   |
| Package 2 Height             | 11.81 in (30 cm)          |
| Package 2 width              | 15.75 in (40 cm)          |
| Package 2 Length             | 23.62 in (60 cm)          |
| Unit Type of Package 3       | PAM                       |
| Number of Units in Package 3 | 200                       |
| Package 3 Weight             | 487.60 lb(US) (221.17 kg) |
| Package 3 Height             | 82.68 in (210 cm)         |
| Package 3 width              | 39.37 in (100 cm)         |
| Package 3 Length             | 47.24 in (120 cm)         |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>           |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |

## Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---