

Product data sheet

Characteristics

A9MEM3465

iEM3465 energy meter - BACnet - 1 DI - 1 DO - multi-tariff - LVCT

Product availability : Stock - Normally stocked in distribution facility



Price* : 539.00 USD



Main

Range	Acti 9
Range of product	Acti 9 iEM3000
Device short name	IEM3465
Product or component type	Energy meter

Complementary

Poles description	3P 1P + N 3P + N
Type of measurement	Active and reactive energy Active and reactive power Current Voltage
Metering type	Active, reactive, apparent energy (signed, four quadrant)
Device application	Sub billing Multi-tariff Partial meter
Accuracy class	Class 0.5S active energy IEC 62053-22 Class 0.5S active energy ANSI C12.20
Input type	split core current transducer 0.333 V or 1 V
Rated voltage	100...277 V +/- 20 % 173...480 V +/- 20 %
Network frequency	60 Hz 50 Hz
Technology type	Electronic
Display type	LCD display
Sampling rate	32 samples/cycle
Measurement current	1...32767000 mA

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

Maximum value measured	99999999.9 kWh 99999999 MWh
Tariff input	Tariff 4)
Communication port protocol	BACnet 9.6, 19.2, 38.4, 57.6, 76.8 kbauds
Communication port support	Screw terminal block RS485
Local signalling	Green indicator light power ON Yellow flashing LED accuracy checking alarm overload
Number of inputs	1 digital 0...5 V/11...40 V 24 V DC
Number of outputs	1 digital (static)
Output voltage	5...40 V DC@50 mA
Mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Current circuit screw terminals 0.01 in ² (6 mm ²) Voltage circuit screw terminals 0.00 in ² (2.5 mm ²) Input/output circuit screw terminals 0.00 in ² (1.5 mm ²) Communication screw terminals 0.00 in ² (2.5 mm ²)
Tightening torque	Input/output circuit 4.43 lbf.in (0.5 N.m) Philips Voltage circuit 4.43 lbf.in (0.5 N.m) Philips Current circuit 7.08 lbf.in (0.8 N.m) pozidriv Communication 4.43 lbf.in (0.5 N.m) Philips
Wire stripping length	Input/output circuit 0.24 in (6 mm) Voltage circuit 0.31 in (8 mm) Current circuit 0.31 in (8 mm) Communication 0.28 in (7 mm)
Standards	UL 61010-1 IEC 62053-21 IEC 61036 IEC 61010 IEC 61557-12 IEC 62053-23
Product certifications	CE IEC 61010 safety) CE EN 61557-12 power monitor) CE IEC 61326-1 EMC) CULus UL 61010 safety) CULus ANSI C12.20 sub-meter) EAC sub-meter) RCM NMI M 6-1 sub-meter) UL

Environment

IP degree of protection	Front panel IP40 IEC 60529 Body IP20 IEC 60529
IK degree of protection	IK08
Pollution degree	2
Relative humidity	5...95 % 97 °F (36 °C)
Ambient air temperature for operation	-13...158 °F (-25...70 °C) - IEC
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Operating altitude	< 9842.52 ft (3000 m)
Color	White
9 mm pitches	10
Width	3.54 in (90 mm)
Height	3.43 in (87 mm)
Depth	2.72 in (69 mm)

Ordering and shipping details

Category	09786 - SE ENTRY POWER METER
Discount Schedule	PL1
GTIN	03606480845239
Nbr. of units in pkg.	1

Package weight(Lbs)	12.66 oz (359 g)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.46 in (8.8 cm)
Package 1 width	3.86 in (9.8 cm)
Package 1 Length	4.13 in (10.5 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.