



Price* : 28.10 USD



Main

Range	Linergy
Product name	HK
Product or component type	Plug outlet
Poles description	1P + N
[I _{th}] conventional free air thermal current	32 A
I ² t on activation	200000 A ² .s
Number of points	1
Number of cables	2 0.01 in ² (4 mm ²)
Cable length	3.28 ft (1 m)
Quantity per set	Set of 6

Complementary

[Ui] rated insulation voltage	600 V CSA 600 V UL 690 V IEC 60439-1
Peak current	25 kA
Width	0.71 in (18 mm)
Height	1.81 in (46 mm)
Depth	1.50 in (38 mm)
Net Weight	0.09 lb(US) (0.04 kg)

Environment

Standards	IEC 60439
Product certifications	DNV UL CSA LROS (Lloyds register of shipping)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

Ordering and shipping details

Category	22623 - PANEL BUS (AK5)
Discount Schedule	I11
GTIN	00785901077800
Nbr. of units in pkg.	6
Package weight(Lbs)	6 lb(US) (2.72 kg)
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.54 in (9 cm)
Package 1 width	9.25 in (23.5 cm)
Package 1 Length	9.25 in (23.5 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Weight	24.02 oz (681 g)
Package 2 Height	3.54 in (9 cm)
Package 2 width	9.25 in (23.5 cm)
Package 2 Length	9.25 in (23.5 cm)
Unit Type of Package 3	S04
Number of Units in Package 3	54
Package 3 Weight	16.21 lb(US) (7.354 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	15.75 in (40 cm)
Package 3 Length	23.62 in (60 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------