Product data sheet Characteristics

HGA261104

Circuit breaker, PowerPact H, I-Line, thermal magnetic, 110A, 2 pole,18 kA, 600 VAC







Main

Range of product	PowerPact H
Product or component type	Circuit breaker

Complementary		Y
Line Rated Current	110 A	<u></u>
Number of Poles	2P	
Breaking capacity code	G	
Mounting mode	I-Line	<u>.</u>
Magnetic hold current	900 A	
Magnetic tripping current	1700 A	
Electrical connection	I-Line connection line Lugs load	
Tightening torque	44.25 lbf.in (5 N.m) 0.000.15 in² (2.595 mm²) (AWG 14AWG 3/0)	
Phase connection	BC	.
Height	9.73 in (247.14 mm)	
Width	2.94 in (74.68 mm)	
Depth	4.8 in (121.92 mm)	
Continuous current rating	80 %	

Environment

Product certifications	CE
	CSA
	IEC
	UL Listed
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01117-HG, HJ, JG, JJ I-LINE BREAKER/SWITC
Discount Schedule	DE2
GTIN	00785901666059
Nbr. of units in pkg.	1
Package weight(Lbs)	3.00 lb(US) (1.361 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	3.88 in (9.843 cm)	
Package 1 width	8.13 in (20.638 cm)	
Package 1 Length	14.63 in (37.148 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months