



Price* : 96.00 USD



Main

Range	Linergy
Product name	HK
Product or component type	Mounting plate
Poles description	1P + N
[I _{th}] conventional free air thermal current	25 A
I ² t on activation	200000 A ² .s
Number of cables	2 0.01 in ² (4 mm ²) 221 °F (105 °C)
Width	2.13 in (54 mm)
Height	4.13 in (105 mm)
Depth	2.40 in (61 mm)

Complementary

[Ui] rated insulation voltage	690 V IEC 60439-1
9 mm pitches	6
Net Weight	0.30 lb(US) (0.135 kg)

Environment

Standards	IEC 60439
Product certifications	UL DNV CSA LROS (Lloyds register of shipping)

Ordering and shipping details

Category	22623 - PANEL BUS (AK5)
----------	-------------------------

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Discount Schedule	I11
GTIN	03389110537406
Nbr. of units in pkg.	1
Package weight(Lbs)	7.37 oz (209 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.48 in (6.3 cm)
Package 1 width	2.87 in (7.3 cm)
Package 1 Length	4.72 in (12 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------