# Product data sheet Characteristics

# LRL36000S40X POWERPACT AUTOMATIC MOULDED CASE SWITCH 600V 400 A L-Frame

Product availability: Non-Stock - Not normally stocked in distribution facility

SQUARE D



Price\*: 8,055.00 USD



#### Main

Product or component type	Automatic switch	
Range of product	PowerPact L	
Trip unit technology	Magnetic	
Circuit breaker type	L-Frame	

#### Complementary

o o mpio montary			
Line Rated Current	400 A		
[Ue] rated operational voltage	600 V AC		
Mounting mode	Unit mount		
Poles description	3P		
Short-circuit withstand	200 kA 240 V UL 489 200 kA 480 V UL 489 100 kA 600 V UL 489		
Breaking capacity code	R	:	
Electrical connection	Lugs line Lugs load		
AWG gauge	AWG 2/0500 kcmil aluminium/copper)		
Terminal identifier	AL600LS52K3		
Magnetic tripping current	4800 A		
Height	13.38 in (339.85 mm)		
Width	5.51 in (139.95 mm)		
Depth	6.61 in (167.89 mm)		
Tightening torque	442.54 lbf.in (50 N.m) 0.110.37 in² (70240 mm²) (AWG 2/0500 kcmil)		

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

#### Environment

Product certifications	UL Listed
	CSA
	IEC

## Ordering and shipping details

Category	01119 - L HIGH INTERUPT UNIT MT BREAKER/SW		
Discount Schedule	DE2		
Nbr. of units in pkg.	1		
Package weight(Lbs)	1 lb(US) (0.45 kg)		
Returnability	Yes		
Country of origin	US		

### Offer Sustainability

Sustainable offer status	Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
REACh Regulation	REACh Declaration		
EU RoHS Directive	Compliant EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	End of Life Information		
PVC free	Yes		

#### Contractual warranty

Warranty	18 months	