Product data sheet Characteristics

JDL36175SA

Circuit breaker, PowerPacT J, unit mount, thermal-magnetic, 175A, 3 pole 14 kA, 600 VAC, shunt trip





Price*: 3,447.00 USD



Main

Product or component type	Circuit breaker

Complementary

Main		
Product or component type	Circuit breaker	
Complementary		
Number of Poles	3P	
Breaking capacity code	D D	
Magnetic hold current	875 A	
Magnetic tripping current	1750 A	
Electrical connection	Lugs load Lugs line	
Tightening torque	230.12 lbf.in (26 N.m) 0.040.15 in² (2595 mm²) (AWG 4AWG 4/0)	
Height	7.52 in (191.01 mm)	
Width	4.12 in (104.65 mm)	
Depth	5 in (127.00 mm)	
Continuous current rating	80 %	
Ordering and shipping details		
Category	01110-HD,JD UNIT MT BREAKER/SWITCH	
Discount Schedule	DE2	
GTIN	00785901835752	
Nbr. of units in pkg.	1	
Package weight(Lbs)	5.27 lb(US) (2.39 kg)	
Returnability	No	
Country of origin	US	

Ordering and shipping details

Jul 30, 2021

<u> </u>	
Category	01110-HD,JD UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901835752
Nbr. of units in pkg.	1
Package weight(Lbs)	5.27 lb(US) (2.39 kg)
Returnability	No
Country of origin	US

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	5.13 in (13.018 cm)	
Package 1 width	7.25 in (18.415 cm)	
Package 1 Length	8.44 in (21.433 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months