Product data sheet Characteristics

HGA360306

Circuit breaker, PowerPact H, I-Line, thermal magnetic, 30A, 3 pole,18 kA, 600 VAC







Main

Range of product	PowerPact H
Product or component type	Circuit breaker

Complementary

Complementary		3
Line Rated Current	30 A	
Number of Poles	3P	<u></u>
Breaking capacity code	G	<u>} \</u>
Mounting mode	I-Line	
Magnetic hold current	350 A	
Magnetic tripping current	750 A	<u>.</u>
Electrical connection	I-Line connection line Lugs load	
Tightening torque	44.25 lbf.in (5 N.m) 0.000.15 in² (2.595 mm²) (AWG 14AWG 3/0)	<u></u>
Phase connection	СВА	<u> </u>
Height	9.73 in (247.14 mm)	. <u></u> 5
Width	4.48 in (113.79 mm)	c
Depth	4.8 in (121.92 mm)	9
Continuous current rating	80 %	

Environment

Duraturat acutifications	III I interes
Product certifications	UL Listed
	CSA
	IEC
	CE
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

<u> </u>	
Category	01117-HG, HJ, JG, JJ I-LINE BREAKER/SWITC
Discount Schedule	DE2
Package weight(Lbs)	4.00 lb(US) (1.814 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

ontractal narrang		
Warranty	18 months	