



Main

| | |
|-----------------------------|--|
| Product or Component Type | Circuit breaker |
| Range | PowerPact P |
| Current Sensor Rating Range | 250 A |
| Rated Current | 250 A |
| Breaking Capacity | 65 kA 240 V AC 35 kA 480 V AC 18 kA 600 V AC |
| Trip Unit Technology | Electronic, harmonic, Micrologic 6.0 H, LSIG |

Complementary

| | |
|-----------------------------|--|
| Certifications | CSA IEC UL Listed |
| Rated operational Voltage | 600 V AC |
| Module Type | P-Frame |
| Mounting Location | Busbar |
| Mounting Mode | Unit mount |
| Poles Description | 3P |
| Circuit Breaker Rating Code | G |
| Electrical Connection | Busbar connection line Busbar connection load |
| Continuous Current Rating | 100 % |
| Device Short Name | A |
| Communicaton Interface | Modbus |
| Height | 12.86 in (326.64 mm) |
| Depth | 8.05 in (204.47 mm) |
| Width | 8.27 in (210.06 mm) |
| Tightening Torque | 442.54 lbf.in (50 N.m) 0.15...0.37 in ² (95...240 mm ²) (AWG 3/0...500 kcmil) |

8.85...11.51 lbf.in (1.0...1.3 N.m)

Ordering and shipping details

| | |
|---------------------|--------------------------|
| Package weight(Lbs) | 32.00 lb(US) (14.515 kg) |
|---------------------|--------------------------|