Product data sheet Characteristics

JGL37150D81SO

Circuit breaker, PowerPacT J, unit mount, thermal-magnetic, 150A, 3 pole 20 kA, 500 VDC

Product availability: Non-Stock - Not normally stocked in distribution facility







Main

Product or component type	Circuit breaker
·	

Complementary

Complementary		· · · · · · · · · · · · · · · · · · ·
Number of Poles	3P	
Breaking capacity code	G	
Magnetic tripping current	350600 A	
Electrical connection	Lugs load Lugs line	
Height	7.52 in (191.01 mm)	
Width	4.12 in (104.65 mm)	
Depth	5 in (127.00 mm)	
Continuous current rating	80 %	

Ordering and shipping details

Category	01115 - HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH	
Discount Schedule	DE2	
Nbr. of units in pkg.	1	
Package weight(Lbs)	5 lb(US) (2.27 kg)	
Returnability	No	
Country of origin	US	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
•	