

Product data sheet

Characteristics

CD326NR

Safety switch, general duty, fusible, 600A,
120/240 VAC, 3 poles, 150 hp, solid neutral,
NEMA 3R



Price* : 7,502.00 USD



Main

Product or component type	Single Throw Safety Switch
Series name	General duty

Complementary

Device composition	Neutral (factory installed)
Disconnecter device type	Fusible disconnect
Short-circuit current	100 kA maximum cartridge
Device mounting	Surface
Number of poles	3
Electrical connection	Lugs
[Ue] rated operational voltage	120/240 V AC
Maximum Horse Power Rating	75 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 150 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52
AWG gauge	AWG 3/0...500 kcmil copper or aluminium
Tightening torque	450 lbf.in (50.84 N.m) (AWG 4...500 kcmil)
Height	49.13 in (1247.90 mm)
Width	25.13 in (638.30 mm)
Depth	8.88 in (225.55 mm)

Environment

Product certifications	CSA
NEMA degree of protection	NEMA 3R galvanized steel

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

Ordering and shipping details

Category	00008-H&HU, 2&3P, N1, 30-200A
Discount Schedule	DE1
GTIN	00785901204787
Nbr. of units in pkg.	1
Package weight(Lbs)	135.00 lb(US) (61.235 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	49.13 in (124.8 cm)
Package 1 width	25.12 in (63.8 cm)
Package 1 Length	8.90 in (22.6 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------