



Main

Product or Component Type	Circuit breaker
Range	PowerPact P
Current Sensor Rating Range	600 A
Rated Current	600 A
Breaking Capacity	65 kA 240 V AC 35 kA 480 V AC 18 kA 600 V AC
Trip Unit Technology	Electronic, basic, ET 1.0I, LI

Complementary

Certifications	IEC UL Listed CSA
Rated operational Voltage	600 V AC
Module Type	P-Frame
Mounting Location	Busbar
Mounting Mode	Unit mount
Poles Description	3P
Circuit Breaker Rating Code	G
Electrical Connection	Busbar connection line Busbar connection load
Continuous Current Rating	80 %
Height	12.86 in (326.64 mm)
Depth	8.05 in (204.47 mm)
Width	8.27 in (210.06 mm)
Tightening Torque	442.54 lbf.in (50 N.m) 0.15...0.37 in ² (95...240 mm ²) (AWG 3/0...500 kcmil) 8.85...11.51 lbf.in (1.0...1.3 N.m)

Ordering and shipping details

Category	01215-PG,H,J,K,L,N UNIT MT BREAKERS
Discount Schedule	DE2
Package weight(Lbs)	32.00 lb(US) (14.515 kg)
Returnability	Yes
Country of origin	US

Contractual warranty

Warranty	18 months
----------	-----------