Product data sheet Characteristics

CD326N


Safety switch, general duty, fusible, 600A, 120/240 VAC, 3 poles, 150 hp, solid neutral, NEMA 1

Product availability: Stock - Normally stocked in distribution facility

SQUARE D



Price*: 5,546.00 USD



Main

Product or component type	Single Throw Safety Switch	
Series name	General duty	- بو ز

Complementary

		:
Line Rated Current	600 A	<u>.</u>
Device composition	Neutral (factory installed)	
Disconnector device type	Fusible disconnect	: :
Short-circuit current	100 kA maximum cartridge	
Device mounting	Surface	<u>, </u>
Number of poles	3	
Electrical connection	Lugs	-
[Ue] rated operational voltage	120/240 V AC	2 2. T
Maximum Horse Power Rating	75 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 150 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	, ,
AWG gauge	AWG 3/0500 kcmil copper or aluminium	
Tightening torque	450 lbf.in (50.84 N.m) (AWG 4500 kcmil)	
Height	45.12 in (1146.05 mm)	
Width	24.88 in (631.95 mm)	
Depth	8.88 in (225.55 mm)	
		.9

Environment

Product certifications	CSA
NEMA degree of protection	NEMA 1 galvannealed steel

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Ordering and shipping details

Category	00008 - H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE1
GTIN	00785901829805
Nbr. of units in pkg.	1
Package weight(Lbs)	123 lb(US) (55.79 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	0.94 ft (0.287 m)	
Package 1 width	2.14 ft (0.653 m)	
Package 1 Length	4.25 ft (1.295 m)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead comis known to the State of California to cause cancer and birth defects or other reprodumore information go to www.P65Warnings.ca.gov		
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	RoHS Regulation China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	

Contractual warranty

	•	
Warranty		18 months