	8	I	7	6		5		4	3	I		2		1	
	PIN # CO					Y						REVISIONS			
-									REV.	REV. DESCRI		PTION DATE		APPRO	√ED
-	4 011								A		RELEASED		4/12/2006		
D		JE (-)													
		ANGE (+)													
_	3 DR/	AIN													
	4 N/C														
	7/8-16UN2 Female Th				<i>—</i> 1	/2''-14NPT					[-
С			1			2 - 14111						TABLE A			_
		-	¥_									P/N			_
	3				M	>	>								_
										ľ	FFIN-4FR-1M-SS		40''	_	
	4	2	.0		ŊĨ	- <	$\langle \rangle$					FFIN-4FR-2N		79"	_
-	~ <u> </u>		•									FFIN-4FR-3N		118"	
		[13.3]									FFIN-4FR-4M			157"	
	.5					6.4				FFIN-4F			1-SS	197"	_
3													A-SS	236"	_
										FFIN-4FR			A-SS	315"	
										FFIN-4FR		FFIN-4FR-10	M-SS	393"	
										FFIN-4FR-1 FFIN-4FR-2		FFIN-4FR-15	M-SS	590''	
												M-SS	786''		
_												FFIN-4FR-25	M-SS	983''	_
												FFIN-4FR-30	M-SS	1179'	•
	MATERIALS:								UNLESS OTHERWISE SPECIFIED):	NAME				
									DIMENSIONS ARE IN INCHES AND [MM]	DRAWN CHECKED	BEM	TITLE:		ORPORATION	
	CABLE:	CRUSH PROOF PROFIBUS CABLE, 18/2 W/ SHIELD. ORANGE PVC JACKET								ENG APPR.					
	SHELL:	STAINLESS S							MFG APPR.						
	CONTACTS:		D COPPER ALL	JOY		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF		300V	MATERIAL	COMMENTS:		SIZE DWG. NO			REV
	O-RING:	BUNA-N				MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF	AMPS TEMP	10A Y@S °C	FINISH				√-4FR-ZZ-SS		A
		ZINC PLATED				MENCOM CORPORATION IS	I CIVIP SPE								