



SHIELDED RJ45

MULTI-CONFIGURATION OUTLET ACCEPTS EUROPEAN, INTERNATIONAL, UK, BRITISH, AUSTRALIA, ASIA, THAILAND, NEMA 13A-250V, 15A-127V [MAXIMUM RATINGS], SHUTTERED CONTACTS, 2 POLE-3 WIRE GROUNDING [2P+E].

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS	
BODY:	EPOXY COATED DIE CAST ALUMINUM	VOLTS:	127V / 250V
GASKET:	THERMOPLASTIC ELASTOMER	AMPS:	15A / 13A
HANDLE:	POLYAMIDE	NEMA/UL EN 60529:	4, 4X, 12 IP65
LEVERS:	STAINLESS STEEL	MOUNTING SCREW SIZE:	M4 (8-32) (304 or 316SS for 4X)
OPERATING TEMPERATURE: (-5°C / +50° C (+23° F / +122° F))		MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)
MOUNTING KIT ORDERED SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT		INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
P/N: D-PIC-MT		WIRE STRIP LENGTH:	10 ~ 11 mm

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
SHIELDED RJ45	CAT. 6A JACK	CAT. 6A JACK

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES AND [MM]

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	
DRAWN BY	DCG
DRAWN DATE	07/12/2021
CHECKED BY	DCG
CHECK DATE	07/13/2021
COMMENTS:	
MATERIAL	
FINISH	
DO NOT SCALE DRAWING	

MENCOM CORPORATION		
TITLE: UNIV RCPT, RJ45S, R; 32		
SIZE B	DWG. NO. DUN-RJ45S-R-32	REV B
SCALE: 2:3	WEIGHT:	SHEET 1 OF 1