H-7



MDC (M12) Series Cordsets

4 Conductor MDC Series Cordsets, 18AWG



Straight Female Cordsets

300 Volt, 4 amps

IP69 Rating





Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
[44] 1.7 [15] .6 M12x1	MDC-4FPX-** (Yellow) MDC-4FPX-**-B (Black)	PVC AWM 4 X 18 AWG 300V, 4A -40°C to +105°C 7.4mm OD	Industry Standard PVC	1. Brown 2. White 3. Blue 4. Black 5. Not Used	M12x1
	MDCP-4FPX-**	Yellow PUR AWM 4 X 18 AWG 300V, 4A -40°C to +80°C 7.4mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		
	MDCW-4FPX-**	Yellow TPE AWM 4 X 18 AWG 300V, 4A -40°C to +80°C 7.4mm OD	Weld Slag Resistant TPE		

^{**} Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult the factory for other lengths.

 $Standard\ coupling\ nut\ is\ nickel\ plated\ brass,\ for\ stainless\ steel\ coupling\ nut\ add\ a\ "-SS"\ suffix.\ (e.g.\ MDC-4FPX-1M\ becomes\ MDC-4FPX-1M-SS)$

^{2~5} Pole females will have all 5 contact holes in the connector.