



## TESF/0

- 2 cable entries M 16 x 1.5
- with fixed switching angle
- Metal enclosure
- Good resistance to oil and petroleum spirit
- For left or right hinged doors
- 141 mm x 115 mm x 21,5 mm
- Simple mounting, [REDACTED]  
[REDACTED] (30 ... 60 mm)

## Data

### Ordering data

|                             |             |
|-----------------------------|-------------|
| eCl@ss number, Version 9.0  | 27-27-06-09 |
| eCl@ss number, Version 11.0 | 27-27-06-09 |
| ETIM number, version 6.0    | EC002591    |
| ETIM number, version 7.0    | EC002591    |

### Approval - Standards

|              |       |
|--------------|-------|
| Certificates | cULus |
|              | CCC   |
|              | EAC   |

### General data

|                                      |                             |
|--------------------------------------|-----------------------------|
| Standards                            | EN 60947-5-1<br>BG-GS-ET-15 |
| Enclosure material                   | Zinc die-cast               |
| Material of the contacts, electrical | Silver-nickel alloy 10      |

|                       |       |
|-----------------------|-------|
| Colour of the housing | Black |
| Gross weight          | 840 g |

### General data - Features

|                              |     |
|------------------------------|-----|
| Mounting outside             | Yes |
| Additional hinge             | Yes |
| Number of auxiliary contacts | 2   |
| Number of safety contacts    | 2   |

### Safety appraisal

|              |                |
|--------------|----------------|
| Standards    | EN ISO 13849-1 |
| Mission Time | 20 Year(s)     |

### Safety appraisal - Safety outputs

|                                   |                      |
|-----------------------------------|----------------------|
| B10d Normally-closed contact (NC) | 2,000,000 Operations |
| B10d Normally open contact (NO)   | 1,000,000 Operations |

### Mechanical data

|                          |                      |
|--------------------------|----------------------|
| Mechanical life, minimum | 1,000,000 Operations |
| Positive break angle     | 14 °                 |
| Opening angle            | 180°                 |

### Mechanical data - Connection technique

|                        |                                                                               |
|------------------------|-------------------------------------------------------------------------------|
| Terminal Connector     | Screw connection                                                              |
| Cable section, minimum | 0.5 mm <sup>2</sup>                                                           |
| Cable section, maximum | 1 mm <sup>2</sup>                                                             |
| Note (Cable section)   | All indications about the cable section are including the conductor ferrules. |

## Mechanical data - Dimensions

|                  |         |
|------------------|---------|
| Length of sensor | 21.5 mm |
| Width of sensor  | 141 mm  |
| Height of sensor | 115 mm  |

## Ambient conditions

|                              |        |
|------------------------------|--------|
| Degree of protection         | IP65   |
| Ambient temperature, minimum | -25 °C |
| Ambient temperature, maximum | +65 °C |

## Ambient conditions - Insulation value

|                                           |        |
|-------------------------------------------|--------|
| Rated insulation voltage $U_i$            | 250 V  |
| Rated impulse withstand voltage $U_{imp}$ | 2.5 kV |

## Electrical data

|                            |                        |
|----------------------------|------------------------|
| Thermal test current       | 2.5 A                  |
| Utilisation category AC-15 | 230 VAC                |
| Utilisation category AC-15 | 2 A                    |
| Utilisation category DC-13 | 24 VDC                 |
| Utilisation category DC-13 | 1 A                    |
| Switching element          | NO contact, NC contact |
| Switching principle        | Creep circuit element  |
| Switching frequency        | 1,200 /h               |

## Scope of delivery

|                      |                  |
|----------------------|------------------|
| Included in delivery | Additional hinge |
|----------------------|------------------|

## Notes

### Note (General)

Closed guard device = 0° in contact switch travel diagrams.

The factory-set switching angle is 3°.

Until the limit of the mechanical life has been reached the angle can increase up to 8° under normal wear-out conditions.

The positive break angle is 5°.

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 10:18 AM