



CSS 14-34F0-S-D-M-ST

- 1 x connector plug M12, 8-pole
- Actuation from side
- without edge monitoring of the enabling pushbutton, suitable for automatic start
- To control positive-guided relay without downstream safety monitoring module
- Suitable as individual or terminal device in series-wiring of standards sensors to replace a safety monitoring module
- Self-monitored series-wiring of up to 30 CSS 34 sensors and one CSS 34F0/F1 sensor for control category 4 to ISO 13849-1
- Thermoplastic enclosure
- Electronic contact-free, coded system
- Misaligned actuation possible
- 27 mm x 108.2 mm x 35 mm
- High repeat accuracy of the switching points
- Max. length of the sensor chain 200 m
- 2 short-circuit proof PNP safety outputs
- Integral cross-short, wire-breakage and external voltage monitoring of the safety cables up to the control cabinet

Data

Ordering data

EAN (European Article Number) 4030661354866

eCl@ss number, Version 9.0 27-27-24-03

eCl@ss number, Version 11.0 27-27-24-03

Approval - Standards

Certificates	TÜV cULus EAC
--------------	---------------------

General data

Standards	IEC 60947-5-3
Active principle	inductive
Housing construction form	Block
Installation conditions (mechanical)	not flush
Sensor topology	Sensor for series wiring
Enclosure material	Glass-fibre, reinforced thermoplastic
Active area	Glass-fibre, reinforced thermoplastic
Gross weight	142 g
Reaction time, maximum	30 ms
Duration of risk, maximum	60 ms

General data - Features

Diagnostic output	Yes
Short circuit detection	Yes
Short-circuit recognition	Yes
Safety functions	Yes
Cascadable	Yes
Input for enabling pushbutton, suitable for automatic start	Yes
Integral System Diagnostics, status	Yes
Number of LEDs	3
Number of semi-conductor outputs with signaling function	1

Number of fail-safe digital outputs	2
Number of Series-wiring of sensors	31

Safety appraisal

Standards	EN ISO 13849-1 IEC 60947-5-3 IEC 61508
Performance level, up to	e
Control category to EN13849	4
PFH-value	3.60×10^{-9} /h
Safety Integrity Level (SIL), suitable for applications in	3
Mission Time	20 Year(s)

Mechanical data

Actuating panels	lateral
Active area	lateral
Actuator switch distance	Actuator CST 180-1 / CST 180-2: 10 mm Actuator CST 34-S-1: 14 mm Actuator CST 34-S-2: 14 mm Actuator CST 34-S-3: 14 mm Actuator CST 34-S-1: 12 mm Actuator CST 34-S-2: 12 mm Actuator CST 34-S-3: 12 mm Actuator CST 180-1 / CST 180-2: 8 mm Actuator CST 34-S-1: 17 mm Actuator CST 34-S-2: 17 mm Actuator CST 34-S-3: 17 mm Actuator CST 180-1 / CST 180-2: 13 mm
Hysteresis (Switch distance), maximum	1.5 mm
Repeat accuracy R R	0.5 mm

Note (Repeat accuracy R)

Axial offset: The long side allows for a maximum height misalignment (x) of sensor and actuator of 36 mm (e.g. mounting tolerance or due to guard door sagging). Increased misalignment, max. 53 mm, possible when the CST 34-S-2 actuator is used. The axial misalignment (y) is max. ± 10 mm (see figure: Operating principle)

Mechanical data - Switching distances according IEC 60947-5-3

Switch distance	10 mm 14 mm
Ensured switch distance "ON"	12 mm
S_{ao}	8 mm
Ensured switch distance	13 mm
"OFF" S_{ar}	17 mm

Mechanical data - Connection technique

Terminal Connector	Connector plug M12, 8-pole
Note	The cable section of the interconnecting cable must be observed for both wiring variants! Cable length and cable section alter the voltage drop depending on the output current

Mechanical data - Dimensions

Length of sensor	35 mm
Width of sensor	27 mm
Height of sensor	108.2 mm

Ambient conditions

Degree of protection	IP65 to EN 60529 IP67 to EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C
Storage and transport temperature, minimum	-25 °C

Storage and transport temperature, maximum	+85 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, amplitude 1 mm
Resistance to shock	30 g / 11 ms
Protection rating	II

Ambient conditions - Insulation value

Rated insulation voltage U_i	32 VDC
Rated impulse withstand voltage U_{imp}	0.8 kV
Overvoltage category	III
Degree of pollution to VDE 0100	3

Electrical data

Voltage type	DC (direct current)
No-load supply current I_0	100 mA
Operating current	600 mA
Required rated short-circuit current to EN 60947-5-1	100 A
Switching frequency, approx.	3 Hz

Electrical data - Fail-safe digital outputs

Rated operating current (safety outputs)	250 mA
Output current, (fail-safe output), maximum	0.25 A
Versions	p-type
Voltage drop U_d , maximum	0.5 V
Current leakage I_r	0.5 mA

Voltage, Utilisation category DC12	24 VDC
---------------------------------------	--------

Current, Utilisation category DC12	0.25 A
---------------------------------------	--------

Voltage, Utilisation category DC13	24 VDC
---------------------------------------	--------

Current, Utilisation category DC13	0.25 A
---------------------------------------	--------

Electrical data - Diagnostic output

Versions	p-type
----------	--------

Voltage drop U_d , maximum	5 V
------------------------------	-----

Voltage, Utilisation category DC12	24 VDC
---------------------------------------	--------

Current, Utilisation category DC12	0.05 A
---------------------------------------	--------

Voltage, Utilisation category DC13	24 VDC
---------------------------------------	--------

Current, Utilisation category DC13	0.05 A
---------------------------------------	--------

Electrical data - Electromagnetic compatibility (EMC)

Interfering radiation	IEC 61000-6-4
-----------------------	---------------

EMC rating	IEC 61000-6-2
------------	---------------

Pin assignment

PIN 1	1A1 Ue: (1)
-------	-------------

PIN 2	X1 Safety input 1
-------	-------------------

PIN 3	A2 GND
-------	--------

PIN 4	Y1 Safety output 1
-------	--------------------

PIN 5	OUT Diagnostic output OUT
-------	---------------------------

PIN 6	X2 Safety input 2
-------	-------------------

PIN 7	Y2 Safety output 2
PIN 8	IN without function

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

Recommendation (actuator)	CST 34-S-2 CST 34-S-3 CST 180-1 CST 180-2 CST 34-S-1
Recommended safety switchgear	PROTECT PSC1 SRB-E-301ST SRB-E-201LC

Notes

Note (General)	Evaluation requirements: dual-channel safety input, suitable for p-type sensors with NO function. The safety-monitoring module must tolerate internal functional tests of the sensors with cyclic switch-off of the sensor outputs for max. 0.5 ms. Short-circuit recognition by the evaluation is not necessary.
----------------	---

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 10:43 AM