



BN 75-11Z-1391

- with Pre-wired cable
- Non-contact principle
- 1 Reed kontakts
- Long life
- 80 mm x 99,5 mm x 55 mm
- Float switch
- Thermoplastic enclosure
- Available with M12 plug-in connector and pre-wired cable

Data

Ordering data

EAN (European Article Number)	4030661008998
eCl@ss number, Version 9.0	27-27-01-05
eCl@ss number, Version 11.0	27-27-01-05
ETIM number, version 6.0	EC002544
ETIM number, version 7.0	EC002544

General data

Active principle	Magnetic drive
Housing construction form	Special construction
Enclosure material	Glass-fibre, reinforced thermoplastic
Active area	Plastic
Gross weight	132 g

General data - Features

Number of openers 1

Number of shutters 1

Mechanical data

Actuating element Magnet

Mechanical life, minimum 1,000,000,000 Operations

Hysteresis (Switch distance),
maximum 3 mm

Mechanical data - Connection technique

Terminal Connector Pre-wired cable

Mechanical data - Dimensions

Length of sensor 55 mm

Width of sensor 80 mm

Height of sensor 99.5 mm

Ambient conditions

Degree of protection IP67

Ambient temperature,
minimum -25 °C

Ambient temperature,
maximum +80 °C

Electrical data

Voltage type AC (alternating current)

Switching voltage, maximum 220 VAC

Switching current, maximum	1 A
Switching capacity, maximum	60 W
Switching capacity, maximum	60 VA
Switching element	NO contact / NC contact
Bounce duration, minimum	0.2 ms
Bounce duration, maximum	0.5 ms

Electrical data - Digital Output

Versions	Reed contacts
----------	---------------

Notes

Note (General)	The switching function is reversed accordingly, if the floater in a changeover contact element is turned upside-down. The operating points listed, apply for water.
----------------	---

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:01 AM