



BN 65-01Z/V

- With pre-wired cable
- Actuation from front
- with bias magnet
- Non-contact principle
- Long life
- Actuating surface and direction of actuation marked by switch symbol
- Construction form Ø 13 mm
- Thermoplastic enclosure
- Actuating distance up to 60 mm depending on actuating magnet and version
- with central mounting

Data

Ordering data

EAN (European Article Number) 4030661009872

eCl@ss number, Version 9.0 27-27-01-05

eCl@ss number, Version 11.0 27-27-01-05

ETIM number, version 6.0 EC002544

ETIM number, version 7.0 EC002544

Approval - Standards

Certificates cULus

General data

Active principle	Magnetic drive
Housing construction form	Cylinder smooth
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	65 g

General data - Features

Suitable for elevators	Yes
bias magnet	Yes
Number of openers	1

Mechanical data

Actuating panels	front side
Actuating element	Magnet
Mechanical life, minimum	1,000,000,000 Operations
Repeat accuracy R R	0.3 mm
Actuating speed, maximum	18 m/s
Mounting	central with threaded flange
Tightening torque of nuts, maximum	3 Nm

Mechanical data - Switching distances according IEC 60947-5-3

Switch distance S_n	5 mm ... 55 mm BP 10S = 5 mm 2 x BP 10S = 10 mm BP 15S = 6 mm BP 34S = 20 mm BP 20S = 15 mm BP 31S = 15 mm BP 11S = 5 mm 2 x BP 11S = 15 mm BP 12S = 10 mm 2 x BP 12S = 25 mm BP 21S = 30 mm 2 x BP 21S = 20 ... 55 mm BP 22S = 25 mm 2 x BP 22S = 15 ... 55 mm BE 20 S = 6 mm
Notice (Switch distance S_n)	Actuating distance up to 55 mm depending on actuating magnet and version. The specified switching distances are applicable for the actuation of individually mounted components without ferromagnetic influence. A change of the distance, either positive or negative, is possible due to ferromagnetic influences. The mutual interference between multiple actuating magnets must be observed.

Mechanical data - Connection technique

Terminal Connector	Cable
Length of cable	1 m
Wire cross-section	0.75 mm ²
Wire cross-section	18 AWG
Material of the Cable mantle	H03VV-F

Mechanical data - Dimensions

Diameter of sensor	13 mm
width across flats	22 BK
Length of sensor	103 mm

Ambient conditions

Degree of protection	IP67 to EN 60529
----------------------	------------------

Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+75 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, amplitude 1 mm
Resistance to shock	30 g, on sine wave oscillation
Resistant to vibration	30 g, on sine wave oscillation

Electrical data

Switching voltage, maximum	250 VAC
Switching current, maximum	3 A
Switching capacity, maximum	120 W
Switching capacity, maximum	120 VA
Switching element	Opener (NC)
Bounce duration, minimum	0.3 ms
Bounce duration, maximum	0.6 ms
Switching frequency, maximum	300 Hz
Switching frequency	1,080,000 /h

Electrical data - Digital Output

Versions	Reed contacts
----------	---------------

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

Recommendation (actuator)	BP 10 S
	2x BP 10 S
	BP 15 S
	BP 34 S
	BP 20 S
	BP 31 S
	BP 11 S
	2x BP 11 S
	BP 12 S
	2x BP 12S
	BP 21 S
	2x BP 21 S
	BP 22 S
	2x BP 22 S
	BE 20 S
Recommendation (actuator, lift switchgear)	BP 10
	2 x BP 10
	BP 15
	BP 34

Notes

Note (General)	The switch is to be mounted on iron with a non-magnetic layer of at least 20 mm.
----------------	--

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 8:59 AM