



BN 85-R-1824-3 1,0M

- Mounting with clamping brackets and sheathed cable
- Actuation from front
- Non-contact principle
- 1 Reed kontakts
- Long life
- Actuating distance up to 40 mm depending on actuating magnet and version
- 40 mm x 35 mm x 16,5 mm
- Thermoplastic enclosure
- Reed-contact to clip-in, on-location assembly

Data

Ordering data

EAN (European Article Number) 4030661023533

eCl@ss number, Version 9.0 27-27-01-05

eCl@ss number, Version 11.0 27-27-01-05

ETIM number, version 6.0 EC002544

ETIM number, version 7.0 EC002544

General data

Active principle Magnetic drive

Housing construction form Block

Enclosure material Glass-fibre, reinforced thermoplastic

Gross weight	35 g
--------------	------

General data - Features

Latching	Yes
Suitable for elevators	Yes
Number of snap-in contacts	1

Mechanical data

Actuating panels	front side
Actuating element	Magnet
Mechanical life, minimum	1,000,000,000 Operations
Actuating speed, maximum	18 m/s
Mounting	Mounting with clamping foot and sheathed cable

Mechanical data - Switching distances according IEC 60947-5-3

Switch distance S_n	2 mm ... 40 mm BP 6S = 2 ... 12 mm BP 8S = 2 ... 10 mm BP 10S = 5 ... 20 mm 2 x BP 10S = 6 ... 27 mm BP 15S = 5 ... 22 mm 2 x BP 15S = 7 ... 28 mm BP 34S = 10 ... 40 mm BP 20S = 3 ... 28 mm BP 31S = 4 ... 30 mm BP 11S = 4 ... 23 mm BP 12S = 5 ... 27 mm
-----------------------	---

Notice (Switch distance S_n)	Actuating distance up to 40 mm depending on actuating magnet and version. The specified switching distances are applicable for the actuation of individually mounted components without ferromagnetic influence. A change of the distance, either positive or negative, is possible due to ferromagnetic influences. The mutual interference between multiple actuating magnets must be observed.
---------------------------------	---

Mechanical data - Connection technique

Terminal Connector	Cable
Length of cable	1 m
Wire cross-section	0.25 mm ²
Wire cross-section	23 AWG
Material of the Cable mantle	LiY

Mechanical data - Dimensions

Length of sensor	16.5 mm
Width of sensor	40 mm
Height of sensor	35 mm

Ambient conditions

Degree of protection	IP40 to EN 60529
Ambient temperature, minimum	+0 °C
Ambient temperature, maximum	+75 °C
Resistance to shock	60 g, on sine wave oscillation

Electrical data

Voltage type	AC (alternating current) DC (direct current)
Switching voltage, maximum	60 VDC
Switching current, maximum	1 A
Switching capacity, maximum	30 W
Switching element	bistable contact

Bounce duration, maximum	0.2 ms
-----------------------------	--------

Electrical data - Digital Output

Versions	Reed contacts
----------	---------------

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

Recommendation (actuator)	BP 10 S 2x BP 10 S BP 15 S BP 34 S BP 20 S BP 31 S BP 11 S BP 12 S BP 6 S BP 8 S 2 x BP 15 S
------------------------------	--

Recommendation (actuator, lift switchgear)	BP 10 BP 6 2 x BP 15 2 x BP 10 BP 15 BP 34
---	---

Notes

Note (General)	The opening and closing functions depend on the direction of actuation, the actuating magnets and the polarity of the actuating magnets.
----------------	--

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:03 AM