



## BN 65-RZ/V

- With pre-wired cable
- Actuation from front
- with bias magnet
- Non-contact principle
- Long life
- Actuating surface and direction of actuation marked by switch symbol
- Construction form Ø 13 mm
- Thermoplastic enclosure
- Actuating distance up to 60 mm depending on actuating magnet and version
- with central mounting

## Data

### Ordering data

EAN (European Article Number) 4030661009933

eCl@ss number, Version 9.0 27-27-01-05

eCl@ss number, Version 11.0 27-27-01-05

ETIM number, version 6.0 EC002544

ETIM number, version 7.0 EC002544

### Approval - Standards

Certificates cULus

### General data

|                           |                                       |
|---------------------------|---------------------------------------|
| Active principle          | Magnetic drive                        |
| Housing construction form | Cylinder smooth                       |
| Enclosure material        | Glass-fibre, reinforced thermoplastic |
| Gross weight              | 70 g                                  |

### General data - Features

|                            |     |
|----------------------------|-----|
| Latching                   | Yes |
| Suitable for elevators     | Yes |
| bias magnet                | Yes |
| Number of snap-in contacts | 1   |

### Mechanical data

|                                    |                              |
|------------------------------------|------------------------------|
| Actuating panels                   | front side                   |
| Actuating element                  | Magnet                       |
| Mechanical life, minimum           | 1,000,000,000 Operations     |
| Repeat accuracy R R                | 0.3 mm                       |
| Actuating speed, maximum           | 18 m/s                       |
| Mounting                           | central with threaded flange |
| Tightening torque of nuts, maximum | 3 Nm                         |

### Mechanical data - Switching distances according IEC 60947-5-3

|                                |                  |
|--------------------------------|------------------|
| Switch distance S <sub>n</sub> | 3 mm ... 45 mm   |
|                                | 2 x BP 10 = 3 mm |
|                                | BP 34 = 15 mm    |
|                                | BP 20 = 10 mm    |
|                                | BP 31 = 10 mm    |
|                                | BP 11 = 15 mm    |
|                                | BP 12 = 20 mm    |
|                                | BP 21 = 45 mm    |
|                                | BP 22 N = 35 mm  |
|                                | BP 22 S = 35 mm  |
|                                | BE 20 = 10 mm    |

|                                          |                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notice (Switch distance S <sub>n</sub> ) | Actuating distance up to 45 mm depending on actuating magnet and version. The specified switching distances are applicable for the actuation of individually mounted components without ferromagnetic influence. A change of the distance, either positive or negative, is possible due to ferromagnetic influences. The mutual interference between multiple actuating magnets must be observed. |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Mechanical data - Connection technique

|                              |                      |
|------------------------------|----------------------|
| Terminal Connector           | Cable                |
| Length of cable              | 1 m                  |
| Wire cross-section           | 0.75 mm <sup>2</sup> |
| Wire cross-section           | 18 AWG               |
| Material of the Cable mantle | H03VV-F              |

### Mechanical data - Dimensions

|                    |        |
|--------------------|--------|
| Diameter of sensor | 13 mm  |
| width across flats | 22 BK  |
| Length of sensor   | 103 mm |

### Ambient conditions

|                              |                  |
|------------------------------|------------------|
| Degree of protection         | IP67 to EN 60529 |
| Ambient temperature, minimum | -25 °C           |

|                                          |                                |
|------------------------------------------|--------------------------------|
| Ambient temperature, maximum             | +75 °C                         |
| Resistance to vibrations to EN 60068-2-6 | 10 ... 55 Hz, amplitude 1 mm   |
| Restistance to shock                     | 15 g, on sine wave oscillation |
| Resistant to vibration                   | 15 g, on sine wave oscillation |

## Electrical data

|                              |                  |
|------------------------------|------------------|
| Switching voltage, maximum   | 250 VAC          |
| Switching current, maximum   | 3 A              |
| Switching capacity, maximum  | 120 W            |
| Switching capacity, maximum  | 120 VA           |
| Switching element            | bistable contact |
| Bounce duration, minimum     | 0.3 ms           |
| Bounce duration, maximum     | 0.6 ms           |
| Switching frequency, maximum | 300 Hz           |
| Switching frequency          | 720,000 /h       |

## Electrical data - Digital Output

|          |               |
|----------|---------------|
| Versions | Reed contacts |
|----------|---------------|

## Scope of delivery

|                      |                                       |
|----------------------|---------------------------------------|
| Included in delivery | Actuators must be ordered separately. |
|----------------------|---------------------------------------|

## Accessory

|                |          |
|----------------|----------|
| Recommendation | 2x BP 10 |
| (actuator)     | BP 34    |
|                | BP 20    |
|                | BP 31    |
|                | BP 11    |
|                | BP 12    |
|                | BP 21    |
|                | BP 22 S  |
|                | BP 22 N  |
|                | BE 20    |

|                             |           |
|-----------------------------|-----------|
| Recommendation              | BP 10     |
| (actuator, lift switchgear) | 2 x BP 10 |
|                             | BP 15     |
|                             | BP 34     |

## Notes

|                |                                                                                  |
|----------------|----------------------------------------------------------------------------------|
| Note (General) | The switch is to be mounted on iron with a non-magnetic layer of at least 20 mm. |
|----------------|----------------------------------------------------------------------------------|

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:00 AM