DATASHEET





SLC 410-E/R0460-90-12

- NOTICE: Not available! (Replacement: SLC 420)
- Control Category 4

Data

Ordering data

Note (Delivery capacity)

Not available!

eCl@ss number, Version 9.0 27-27-27-04

eCl@ss number, Version 11.0 27-27-24

General data

Standards IEC/EN 61496-1/-2

Enclosure material Aluminium

Reaction time, maximum 6 ms

General data - Features

Beam coding available Yes

Integral System Diagnostics, status Yes

Integral System Diagnostics Yes

Number of beams 7

Number of fail-safe digital outputs 2

Safety appraisal

Safety type in accordance with IEC 61496-1

Mechanical data

Height of the protection field 460 mm

Range, protection field, minimum 0 mm

Range, protection field, maximum 18,000 mm

Wave length of the sensor 950 nm

Mechanical data - Connection technique

Terminal Connector Connector

Terminal connector, Recipient Connector plug M12, 5-pole

Terminal, Connector, Transmitter Connector plug M12, 5-pole

Length of the connectable cable, maximum 100 m

Mechanical data - Dimensions

Length of sensor 35 mm

Width of sensor 45 mm

Height of sensor 561 mm

Ambient conditions

Degree of protection IP65 to EN 60529

Ambient temperature, minimum +0 °C

Ambient temperature, maximum +55 °C

Storage and transport temperature, -20 °C

minimum

Storage and transport temperature,

maximum

+70 °C

Protection rating III

Electrical data

Voltage type DC (direct current)

Switching voltage OSSD, HIGH signal 24 V

Electrical power consumption of the receiver 3 W

Electrical power consumption of the

transmitter

2 W

Electrical data - Fail-safe digital outputs

Output current, (fail-safe output), maximum 0.5 A

Versions p-type

Scope of delivery

Included in delivery Emitter + receiver, mounting angle, T-slot nuts

Accessory

Recommended safety switchgear SCR 402R-301

Notes

Note (General) $I_{\rm m}$ In case of failure (interruption of the 0 V supply) the maximum

leakage current is 0.3 mA.

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 10:51 AM