



SLB 400-R50-21P

- NOTICE: Not available! (Replacement: SLB440)
- Range 15 m
- connector plug can be rotated

Data

Ordering data

Note (Delivery capacity)	Not available!
EAN (European Article Number)	4030661286778
eCl@ss number, Version 9.0	27-27-27-01
eCl@ss number, Version 11.0	27-27-27-01

Approval - Standards

Certificates	IFA
--------------	-----

General data

Standards	IEC/EN 61496
Enclosure material	Plastic
Gross weight	39 g
Reaction time, maximum	25 ms
Note (Lateral force at bolt return)	Only in combination with safety monitoring module

General data - Features

Receiver	Yes
Integral System Diagnostics, status	Yes

Safety appraisal

Safety type in accordance with IEC 61496-1	4
--	---

Mechanical data

Range, protection field, minimum	0 mm
Range, protection field, maximum	15,000 mm
Wave length of the sensor	880 nm

Mechanical data - Connection technique

Terminal Connector	Connector M12
Terminal connector, Recipient	Connector plug M8, 4-pole, can be rotated

Mechanical data - Dimensions

Length of sensor	63.5 mm
Width of sensor	17 mm
Height of sensor	50 mm

Ambient conditions

Degree of protection	IP67 to EN 60529
Ambient temperature, minimum	+0 °C
Ambient temperature, maximum	+60 °C
Storage and transport temperature, minimum	-20 °C
Storage and transport temperature, maximum	+80 °C

Protection rating	0
-------------------	---

Electrical data

Length of cable, maximum	100 m
--------------------------	-------

Electrical data - Digital Output

Versions	Only in combination with safety monitoring module SLB 400-C
----------	---

Status indication

Indicated operating states	soiling switching condition
----------------------------	--------------------------------

Accessory

Recommended safety switchgear	SLB 400-C10-1R
-------------------------------	----------------

Notes

Note (Restart interlock)	Only in combination with safety monitoring module
--------------------------	---

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 12:27 PM