



SRB302X3-24/115V

- Suitable for the signal processing of outputs with contact sensors
- Suitable for signal processing of outputs connected to potentials (AOPDs), e.g. safety light grids/curtains
- 3 safety contacts, STOP 0
- 2 Signalling outputs

Data

Ordering data

Note (Delivery capacity)	Not available!
EAN (European Article Number)	4250116202157
eCl@ss number, Version 9.0	27-37-18-19
eCl@ss number, Version 11.0	27-37-18-19
ETIM number, version 6.0	EC001449

Approval - Standards

Certificates	cULus EAC
--------------	--------------

General data

Standards	IEC 61508 IEC/EN 60204-1 EN 60947-5-1 EN ISO 13849-1
Climatic stress	EN 60068-2-78
Enclosure material	Glass-fibre reinforced thermoplastic, ventilated

Material of the contacts, electrical	AgSn0. self-cleaning, positive drive
Gross weight	520 g

General data - Features

Stop-Category	0
Electronic Fuse	Yes
Wire breakage detection	Yes
Short-circuit recognition	Yes
Start input	Yes
Feedback circuit	Yes
Automatic reset function	Yes
Reset edge detection	Yes
Earth connection detection	Yes
Integral System Diagnostics, status	Yes
Number of auxiliary contacts	2
Number of LEDs	3
Number of openers	2
Number of safety contacts	3

Safety appraisal

Standards	EN 60947-5-1 IEC 61508
-----------	---------------------------

Safety appraisal - Relay outputs

Performance Level, up to	e
Control category to EN13849	4
Diagnostic Coverage (DC) Level	> 99 %
PFH-value	2.00×10^{-8} /h

Safety Integrity Level (SIL), suitable for applications in	3
Mission time	20 Year(s)
Common Cause Failure (CCF), minimum	65

Mechanical data

Mechanical life, minimum	10,000,000 Operations
Mounting	Snap onto standard DIN rail to EN 60715

Mechanical data - Connection technique

Terminal Connector	Screw connection rigid or flexible
Terminal designations	IEC/EN 60947-1
Cable section, minimum	0.25 mm ²
Cable section, maximum	2.5 mm ²
Tightening torque of Clips	0.6 Nm

Mechanical data - Dimensions

Width	45 mm
Height	100 mm
Depth	121 mm

Ambient conditions

Degree of protection of the enclosure	IP40
Degree of protection of the mounting space	IP54
Degree of protection of clips or terminals	IP20

Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C
Storage and transport temperature, minimum	-40 °C
Storage and transport temperature, maximum	+85 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, Amplitude 0.35 mm
Resistance to shock	30 g / 11 ms

Ambient conditions - Insulation value

Rated impulse withstand voltage U _{imp}	4 kV
Overvoltage category	III
Degree of pollution to VDE 0110	2

Electrical data

Frequency range	50 Hz 60 Hz
Rated operating voltage	24 VAC -15% / +10% 24 VDC -15%/+20%, residual ripple max. 10% 115 VAC -15% / +10%
Rated AC voltage for controls, 50 Hz, minimum	20.4 VAC 26.4 VAC
Rated control voltage at AC 50 Hz, maximum	126.5 VAC 97.8 VAC
Rated AC voltage for controls, 60 Hz, minimum	20.4 VAC 26.4 VAC
Rated control voltage at AC 60 Hz, maximum	126.5 VAC 97.8 VAC
Rated AC voltage for controls at DC minimum	20.4 VDC
Rated control voltage at DC, maximum	28.8 VDC

Utilisation category AC-15	230 VAC
Utilisation category AC-15	6 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	6 A
Electrical power consumption	2.5 W
Electrical power consumption	5 VA
Contact resistance, maximum	0.1 Ω
Note (Contact resistance)	in new state
Drop-out delay in case of power failure, typically	60 ms
Drop-out delay in case of "emergency stop", maximum	20 ms
Pull-in delay at RESET, typically	20 ms

Electrical data - Digital inputs

Conduction resistance, maximum	40 Ω
--------------------------------	-------------

Electrical data - Electromagnetic compatibility (EMC)

EMC rating	EMC-Directive
------------	---------------

Status indication

Indicated operating states	Position relay K2 Position relay K1
----------------------------	--

Other data

Note (applications)	Guard system Emergency-Stop button Pull-wire emergency stop switches Safety light curtain
---------------------	--

Notes

Note (General)

Inductive loads (e.g. contactors, relays, etc.) are to be suppressed by means of a suitable circuit.

Circuit example

Note (Wiring diagram)

The wiring diagram is shown with guard doors closed and in de-energised condition.

Relay outputs: Suitable for 2 channel control, for increase in capacity or number of contacts by means of contactors or relays with positive-guided contacts.

The control recognises cross-short, cable break and earth leakages in the monitoring circuit.

2 channel control shown for a guard-door monitor with two contacts, of which at least one contact has positive break, with external reset button (R).

(H2) = Feedback circuit

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:06 AM