

RJ45 CAT.5 Hirose TM11



Application advantage

- Suitable for 26 AWG stranded conductors
- Anti-kink protection
- Screened against EMI
- Bend protection & guide plate included

Approvals



Contact tools



Hirose
crimp tool
page 262

Part number	Conductor size	Max. cable outer diameter		Pack size
		in	mm	
CE6321	26 AWG	0.228	5.8	50

RJ45 CAT.5 Stewart SS37



Application advantage

- Suitable for 26 AWG stranded conductors
- Anti-kink protection
- Screened against EMI
- Bend protection & guide plate included

Approvals



Contact tools



Stewart
crimp tool
page 262

Part number	Conductor size	Max. cable outer diameter		Pack size
		in	mm	
CE6323	26 AWG	0.255	5.7	50

RJ45 CAT.5e FM45, field wireable



Application advantage

- Suitable for solid and stranded conductors
- Provides IP20 protection
- Tool-free, re-switchable field termination
- Tension- and vibration-resistant
- Can accommodate both screened and unscreened cables
- IDC/piercing terminal acc. to IEC 60352-4

Approvals



Part number	Conductor size	Max. cable outer diameter		Pack size
		in	mm	
21700540	26 - 23 AWG*	0.315	8.0	1

* 22 AWG is possible, with restrictions.