


SKINDICHT® SVF

Brass strain relief connectors for flat & festoon cable with PG thread



Complete the installation



SKINDICHT®
SM locknuts
page 542

The SKINDICHT® SVF is a compact strain relief connector made of nickel-plated brass for flat cable. The special neoprene bushing provides a flexible seal over a wide range of cable widths. Ideal for use with ÖLFLEX® FLAT, ÖLFLEX® LIFT F, or ÖLFLEX® CRANE F.

Approvals



Technical data

	Material:		IP Protection:	IP54
	- body:	nickel-plated brass	Locknuts:	add SKINDICHT® SM, page 542
	- seal:	neoprene bushing		
	Temperature range:	-20°C to +100°C		

Part number	Thread	Minimum flat cable width		Maximum flat cable width		Minimum cable thickness		Maximum cable thickness		Wrenching flats		Overall length (C) in	Thread length (D) in	Pack size
		in	mm	in	mm	in	mm	in	mm	(SW1) in	(SW2) in			
52005480	PG 16	—	—	0.630	16	—	—	0.197	5	0.946	0.867	1.08	0.26	25
52005490	PG 21	0.355	9	0.827	21	0.118	3	0.315	8	1.182	1.103	1.18	0.28	25
52005500	PG 29	0.552	14	1.182	30	0.158	4	0.453	11.5	1.576	1.458	1.24	0.32	10
52005510	PG 36	0.946	24	1.576	40	0.158	4	0.453	11.5	1.970	1.852	1.42	0.35	10
52005520	PG 42	1.143	29	1.773	45	0.197	5	0.473	12	2.246	2.128	1.58	0.39	5
52005530	PG 48	1.340	34	1.970	50	0.197	5	0.473	12	2.522	2.364	1.64	0.39	5