

MTS 1-PHASE CONTROL AND ISOLATION TRANSFORMER

P: 100VA IN: 208...550VAC OUT: 2x115VAC

Single-phase - Control and Isolation Transformers
100 VA
Isolation class T 40/B
Other voltages on request.

Link to Product

Illustration



Product may differ from Image



General data	
Standards	EN 61558-1, EN 61558-2-4, EN 62041 category 0
Mounting method	Long-hole mounting or DIN-rail mountable TH35 (EN 60715)
Temperature range	-20...+40 °C (storage temperature -20...+80 °C)
Test isolation voltage	4 kV (prim./sec.)
Drill hole Ø	4.8x8.4 mm
Fixing centers a×b×c	64.5×64 mm

Dimensions H×W×D 105×84×98 mm

Output

Output voltage 1× 230, 1× 115, 2× 115 V AC
Output rating 100 VA

Input

Input voltage 208, 230, 380, 400, 420, 440, 460, 480, 500, 525, 550 V AC
Inrush current 9.9 A (208 V AC); 3.8 A (550 V AC)
Short-circuit current 7.6 A (208 V AC); 2.9 A (550 V AC)
Input current 0.57 A (208 V AC); 0.21 A (550 V AC)
Frequency 50...60 Hz

Product article number of manufacturer 86143