

MST 1-PHASE CONTROL AND ISOLATION TRANSFORMER

P: 250VA IN: 208...550VAC OUT: 2x115VAC

Single-phase - Control and Isolation Transformers  
250 VA  
Isolation class T 40/B  
Other voltages on request.

Link to Product

Illustration



Product may differ from Image



| General data           |                                                 |
|------------------------|-------------------------------------------------|
| Standards              | EN 61558-1, EN 61558-2-4, EN 62041 category 0   |
| Mounting method        | Key-hole mounting                               |
| Temperature range      | -20...+40 °C (storage temperature -20...+80 °C) |
| Test isolation voltage | 4 kV (prim./sec.)                               |
| Drill hole Ø           | 5.8×10 mm                                       |
| Fixing centers a×b×c   | 74.4×90 mm                                      |

Dimensions H×W×D 104×120×122 mm

**Output**

Output voltage 1× 230, 1× 115, 2× 115 V AC  
Output rating 250 VA

**Input**

Input voltage 208, 230, 380, 400, 420, 440, 460, 480, 500, 525, 550 V AC  
Inrush current 26 A (208 V AC); 9.6 A (550 V AC)  
Short-circuit current 25 A (208 V AC); 9.2 A (550 V AC)  
Input current 1.36 A (208 V AC); 0.51 A (550 V AC)  
Frequency 50...60 Hz

Product article number of manufacturer 86145