



MPS POWER SUPPLY 1-PHASE,

IN: 185-265VAC OUT: 22-28V/10ADC

INPUT: 185...265 V AC
OUTPUT: 22...28 V DC
Current: 10 A
Units decoupling through diode block at parallel usage.

Link to Product

Illustration



Product may differ from Image



General data	
Standards	IEC 61010-2-201, EN 61204-3, EN 55022 B
Mounting method	DIN-rail mountable TH35 (EN 60715), additional plate for screw mounting Art.-No. 89500
Temperature range	0...+60 °C (storage temperature -25...+85 °C)
Relative humidity	5...95%, no condensation
Efficiency	90%
Dimensions HxWxD	132x198x97 mm

Output	
Output voltage	24 V DC (SELV), $\pm 1\%$; 22...28 V adjustable
LED display	LED (green): in operation; LED (red): off; LED (yellow): pre-warning when overheated or overloaded
Alarm output	electronic relay max. 60 V DC/0.2 A, group alarm for all failures and pre-warnings, reset via the green button
Output current	10 A (+60 °C); 12 A (+40 °C)
Mains failure bridging time	min. 10 ms (230 V AC)
Ripple	max. 20 mV eff/rms
Spikes	max. 100 mV ss/pp
Unit protection	short-circuit and overload protected
Parallel usage/serial usage	yes/yes
Input	
Input voltage	185...265 V AC
Primary fusing external	max. 10 A
Input current	2.1 A
Frequency	50...60 Hz
Product article number of manufacturer	85055